# LEONARDO 370 EVO VCS TOP - 15"

Full-size, straight-feed slicer, for fresh meat and bolas





- 15" high-quality, heavy-duty straight-feed fresh meat slicers
- Specially designed double-feed carriage to support fresh meat
- Ideal for meat depts, butcheries and carnicerias. Perfect for bola (bistecs, arranchera and milanesa)
- The TOP version provides even higher durability in terms of reduced maintenance costs with:
  - all knobs, handles, dials and feet in aluminum
  - a fully sealed and waterproof IP 67 switch, with stainless steel on/off buttons
  - no volt release prevents inadvertent reactivation after a power outage
  - complete stainless steel drive shaft assembly

## Features

#### Technica

- The special carriage allows you to slice any kind of raw meat
- The sharpener assembly is made entirely from aluminum, no plastic that may break with heavy use.
- The tie rod assembly and all screws are made of stainless steel for longer life.
- The slide shaft is made of ground, chromed steel for a smoother operation.
- The high-quality bushings and ball bearings are self-lubricating.
- The dial thickness control cam system allows for an always precise cut.

#### Safety

- A safety cover is placed under the motor and the electrical components.
- The hopper features an exclusive heavy duty plastic protection to keep operator's hand at a safe distance from the blade while operating slicer

## Sanitary

- Easy to clean aluminum alloy construction does not crack or stain.
- The screws are stainless steel and resist wear and oxidation.
- The carriage and the center plate are quickly removable without tools.

# **Specifications**

**Operation:** Straight Feed.

**Construction:** Polished, anodized aluminum alloy.

Knife 350: 15" (370 mm), one piece, chromium plated 100Cr6 forged

carbon steel blade.

**Sharpener:** Built-in, removable, two stone dual action. **Slice thickness:** Infinitely variable up to 13/16"

Motor: Infinitely variable up to 13/16"

1/2 Hp (410 W), belt driven, fan cooled.

**Electrical:** 120V AC, 60Hz, 3.10 Amp. (220V, 50Hz available on request).

Plug and Cord: Attached, flexible, 3 wire SJT AWG 16, 6'4" long,

NEMA 5-15 P

**Controls:** ON/OFF stainless steel keypad, IP 67 waterproof protection.

No voltage release.





Removable end weight pusher



Increased gap between blade and machine body



Dual-stage cam allows precise thin and thick slicing



Stainless steel slice deflector




Carriage buffer





Built-in sharpener



Sealed electrical enclosure







| Ø Blade<br>Motor                                 | Cut thickness<br>Blade rpm | Carriage stroke | Hopper   | A В      | С       | D        | E      | F       | G        | Х         | Υ       | Н       | W       | Net weight | Shipping        | Gross weight |
|--|----------------------------|-----------------|--|----------|---------|----------|--------|---------|----------|-----------|---------|---------|---------|------------|-----------------|--------------|
| mm/inch watt/Hp                                  | inch. rpm                  | inch.           | inch. inc  | h. inch. | inch.   | inch.    | inch.  | inch.   | inch.    | inch.     | inch.   | inch.   | inch.   | lbs.       | inch.           | lbs.         |
| <b>Leonardo 370 EVO VCS TOP</b> 370/15" 410-0,55 | 1" 216                     | 149/16"         | 16 <sup>59/64</sup> " x 11 <sup>13/16</sup> " 22 <sup>14</sup> | 169/64"  | 299/64" | 2811/32" | 235/8" | 335/64" | 2513/64" | 11 39/64" | 105/32" | 105/32" | 105/32" | 124        | 33" x 34" x 33" | 200          |