



Potato Peeler PI-10

10 KG. / 22 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.
0-6 min. timer.
Removable plate for easy cleaning.**

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purposes.
- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Liftable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stainless steel floor stand.
- Filter with no-foam feature.

TECHNICAL SPECIFICATIONS

Hourly production: 450 lbs. / 550 lbs.
Capacity per load: 22 lbs.
Timer (min-max): 0' - 6'
Total loading: 0.75 Hp

Electrical supply: 120V / 60 Hz / 1~ (5 A)

External dimensions (WxDxH)

- Width: 17 "
- Depth: 25 "
- Height: 24.6 "

External dimensions with stand

- Width with stand: 17 "
- Depth with stand: 25.1 "
- Height with stand: 41 "

Net weight: 86 lbs.

