

Vacuum packing machine SU-316GP+ 120/50-60/1



SPECIFICATIONS SHEET

No existe en el sistema la plantilla Portal - USA para el ítem 1140758

DEFAULT EQUIPMENT

- BUSCH pump.
- Sensor Controls.
- 25 programmable settings.
- Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- Soft air function.
- Clear methacrylate lid.
- "PAUSE" function.
- Liquid detection system.

OPTIONAL EQUIPMENT

- Inert gas
- Sealing plus
- Printer
- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories
- Support for liquid packaging
- Additional filling plates



Vacuum packing machine SU-316GP+ 120/50-60/1

TABLETOP MODEL. 16 M³/H. 320 MM.

320 mm. sealing bar.
16 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber. Deep-drawn chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.
- NSF-listed model.

