

10" Dual Cartridge Water Filtration System

Food Service System Housing for Drop-In Cartridges

Features

- 10" low profile slim line dual bowl housing made from durable polypropylene for excellent chemical resistance
- · Equipped with a pressure relief button to relieve water pressure during cartridge changes
- Includes 9 3/4" granular activated carbon/ phosphate (item #790PSC10) and 9 7/8" sediment (item #790SDC10) drop-in cartridges
- · Includes wall mounting bracket
- · Shipped fully assembled

Technical Data

Dimensions	14 1/4"W x 5 3/4"D x 14 1/2"H
Inlet Connection	1/2"
Outlet Connection	1/2"
NPT Ports	Female
Opaque Housing	Polypropylene
Сар	Polypropylene
Maximum Temperature	125°F (51.7°C)
Maximum Pressure	75 PSI (5.17 bar)

Installation & Operation Tips

- · Choose a mounting location suitable to support the full weight of the system when operating
- · Install vertically so bowl hangs down
- · Make sure O-ring is sufficiently lubricated
- · Always screw on bowls by hand; never tighten with a housing wrench
- Change cartridges on a 6 month preventative maintenance program
- · Clean bowl with mild solution of detergent before inserting new cartridge
- · Always flush the filter cartridge at time of installation and cartridge change

Applications

- Designed specifically for countertop steamers, but also ideal for small beverage equipment.
- For use where sediment is present and water is not pre-filtered
- Improves water's taste and filters out scale and odors.



