

AQUAKING 22

#790FILTER22 KIT

20" Dual Cartridge Water Filtration System

Food Service System Housing for Drop-In Cartridges

Features

- 20" low profile slim line dual bowl housing made from durable polypropylene for excellent chemical resistance
- Equipped with a pressure relief button to relieve water pressure during cartridge changes
- Includes 20" granular activated carbon/phosphate (item #790PSC20) and 20" sediment (item #790SDC20) drop-in cartridges
- Includes wall mounting bracket
- Shipped fully assembled

Technical Data

Dimensions	17 3/8"W x 6 1/2"D x 24 3/4"H
Inlet Connection	1/2"
Outlet Connection	1/2"
NPT Ports	Female
Opaque Housing	Polypropylene
Cap	Polypropylene
Maximum Temperature	125° F (51.7 °C)
Maximum Pressure	100 PSI (6.89 bar)

Installation & Operation Tips

- Choose a mounting location suitable to support the full weight of the system when operating
- Install vertically so bowl hangs down
- Make sure O-ring is sufficiently lubricated
- Always screw on bowls by hand; never tighten with a housing wrench
- Change cartridges on a 6 month preventative maintenance program
- Clean bowl with mild solution of detergent before inserting new cartridge
- Always flush the filter cartridge at time of installation and cartridge change

Applications

- Ideal for many residential, commercial and light industrial applications, such as floor model steamers.
- For use where sediment is present and water is not pre-filtered.
- Improves water's taste and filters out scale and odors.

