



Product Specification Sheet - 11492

11492	Black Melamine Round Serving Tray 15" Dia. x 2"				
Country of Origin	CN	Harmonized Tariff Code	3924.10.3000	Minimum Order Quantity	1 EA

Item Specifications

Individual Unit	Length	Width	Height	Piece Weight	1.881 (lbs)	0.853 (kg)	UPC Label on Product?	Yes
	15 (in)	15 (in)	2 (in)	Unit Measure Net Weight	1.881 (lbs)	0.853 (kg)	UPC Application	Hang Tag
	38 (cm)	38 (cm)	5 (cm)	Unit Measure Gross Weight	2.500 (lbs)	1.134 (kg)	BPA Free	Yes
				Individual Unit Cube	0.3975 (ft³)	0.01126 (m³)	NSF	No
	Min. Temp.	32 (°F)	0 (°C)				Dishwasher Safe	Yes
	Max Temp.	212 (°F)	100 (°C)				Microwave Safe	No

Component	Material	ItemNumber	Material Detail	Origin	Gauge	Diameter	Weight
Tray	Melamine		White Interior w/ Pattern, Gray Exterior	China		15 (in)	853 (g)

Packaging and UPC Information

	Packaging	Quantity	Length	Width	Height	Weight	Cube	Plastic Waste	Paper Waste	UPC
Piece Packaging	Hang Tag Poly Bag, Poly Foam Sheet	1 EA	15 (in) 38.1 (cm)	15 (in) 38.1 (cm)	2 (in) 5.1 (cm)	1.903 (lbs) 0.9 (kg)	0.26 (ft³) 0.007 (m³)			727875270948
Inner Carton	5 Ply Corrugated Carton	2 EA	15.75 (in) 40.0 (cm)	4.75 (in) 12.1 (cm)	15.5 (in) 39.4 (cm)	4.44 (lbs) 2.0 (kg)	0.67 (ft³) 0.019 (m³)			10727875270945
Master Carton	5 Ply Corrugated Carton	4 EA	16.25 (in) 41.3 (cm)	10.25 (in) 26.0 (cm)	16.5 (in) 41.9 (cm)	10 (lbs) 4.5 (kg)	1.59 (ft³) 0.045 (m³)			30727875270949

Pallet Specifications

TI (cartons/layer)	4	HI (layers/pallet)	8	Total Cartons	32	Total Units	128	Pallet Height	87 (in)
--------------------	---	--------------------	---	---------------	----	-------------	-----	---------------	---------

Product Notes	Packaging Details
	A generic hang tag is attached to each tray with a lock tie. Each tray is placed into a poly bag. Poly bags must be either heat sealed or taped closed, and require two punched holes and multilingual suffocation warnings. Trays are then packed 2 EA per inner carton (5 Ply Corrugate). Trays are then packed 4 EA per master carton (5 Ply Corrugate). A total of four UPC labels are applied to two opposite corners of each inner and master carton.



NO IMAGE
AVAILABLE