

HOT WATER DISPENSERS



WB5NL



WB5GT63000



WB-10



WB-14

FEATURES AT A GLANCE

- G3 Digital Control Module – Provides precise control of temperature aeration
- Agitation Pump – On-demand aeration improves tea extraction and food flavor
- Easy-To-Operate – Simple graphic design for all operating functions and ready lights
- Energy Savings Mode – 4 hours after last dispense, tank will maintain temperature of 140°
- Automatic Refill System – For hot water on-demand anytime

Electrical Supply Requirements

MODEL #	DESCRIPTION	PHASE	VOLTS	AMPS	HEATING CONFIG	WIRE	WATTS	HERTZ	GAL/HR	
WB5N	Electric with Aerator, 5 Gallon	1PH	120/220V	12.5/22.7A	2X2500W	2/3W+G	1500/5000W	50/60 Hz	4.5/15.0	NEW
WB5NL	Electric w/Aerator, Low Faucet, 5 Gallon	1PH	120/220V	12.5/22.7A	2X2500W	2/3W+G	1500/5000W	50/60 Hz	4.5/15.0	NEW
WB5GT63000	Electric with Aerator, 5 Gallon	1PH	120/220V	12.5/22.7A	2X2500W	2/3W+G	1500/5000W	50/60 Hz	4.5/15.0	
WB5GT19000	Electric with Aerator, 5 Gallon	3PH	220V	19.7A	3X2500W	4W+G	7500W	50/60 Hz	21.5	
WB-10-12	Electric, 10 Gallon	1PH	120/220V	17.3/31.8A	2X3500W	2/3W+G	2080/7000W	50/60 Hz	5.9/20.0	
WB-14-11	Gas with Sight Glass, 14 Gallon	1PH	115V	3.0A	N/A	2W+G	N/A	50/60 Hz	15.0	
WB-14-12	Electric with Sight Glass, 14 Gallon	1PH	120/220V	17.3/31.8A	2X3500W	2/3W+G	2080/7000W	50/60 Hz	6.1/21.0	

EXPORT

WB5GT3000	Electric with Aerator, 5 gallon	1PH	220V	22.7A	2X2500W	2W+G	5000W	50/60 Hz	15.0
WB-10-60	Electric, 10 Gallon	1PH	220V	31.8A	2X3500W	2W+G	7000W	50/60 Hz	20.0
WB-14-60	Electric with Sight Glass, 14 Gallon	1PH	220V	31.8A	2X3500W	2W+G	7000W	50/60 Hz	21.0

Dimensions

MODEL #	HEIGHT	WIDTH	DEPTH	SHIP WEIGHT	SHIP CUBE
WB5N	25.75"	7.50"	24.38"	42.9 lbs.	9.44 cu. ft.
WB5NL	25.75"	7.50"	24.38"	42.9 lbs.	9.44 cu. ft.
WB5GT63000	24.50"	9.25"	22.00"	39.0 lbs.	5.73 cu. ft.
WB5GT19000	24.50"	9.25"	22.00"	39.0 lbs.	5.73 cu. ft.
WB-10-12	30.88"	16.88"	18.00"	35.0 lbs.	6.5 cu. ft.
WB-14-11	23.75"	24.13"	20.38"	47.0 lbs.	11.62 cu. ft.
WB-14-12	23.75"	27.63"	20.38"	50.0 lbs.	11.62 cu. ft.
WB5GT3000	24.50"	9.25"	22.00"	39.0 lbs.	5.73 cu. ft.
WB-10-60	30.88"	16.88"	18.00"	35.0 lbs.	6.5 cu. ft.
WB-14-60	23.75"	24.13"	20.38"	47.0 lbs.	11.62 cu. ft.

Water Supply Requirements

MODEL #	WATER CONNECTOR	WATER PRESSURE	MIN. FLOW RATE
WB5N	1/4" Flare	20 - 90 psi	1.0 GPM
WB5NL	1/4" Flare	20 - 90 psi	1.0 GPM
WB5GT63000	1/4" Flare	20 - 90 psi	1.0 GPM
WB5GT19000	1/4" Flare	20 - 90 psi	1.0 GPM
WB-10-12	1/4" Flare	20 - 90 psi	1.0 GPM
WB-14-11	1/4" Flare	20 - 90 psi	1.0 GPM
WB-14-12	1/4" Flare	20 - 90 psi	1.0 GPM
WB5GT3000	1/4" Flare	20 - 90 psi	1.0 GPM
WB-10-60	1/4" Flare	20 - 90 psi	1.0 GPM
WB-14-60	1/4" Flare	20 - 90 psi	1.0 GPM

Dispenser Included
 Dispenser Not Included
 Quick Ship
 New Product