

Technical data sheet for

E32D5 ON THE P8M Proofer/Holding Cabinet Full Size Digital / Electric Convection Oven 8 Tray Manual / Electric Proofer/Holding Cabinet



E32D5 OVEN



E32D5

Unit shall be a Moffat electrically heated Turbofan convection oven E.T.L. listed and NSF-4 listed. The oven shall have a one piece porcelain enameled oven chamber, stainless top and sides and safe touch vented easy clean side hinged door that offers field reversible hinging. Oven shall have capacity for five full size sheet pans. The oven shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven control shall allow both manual and programmed operating modes with programmable moisture injection, 2 speed oven fan, and 3 stage cooking. A core temperature probe M236060 is optional. The unit shall include dual halogen oven lamps. Unit shall be supplied in 100% recyclable shipping packaging. This unit shall be Energy Star certified.

P8M

Unit shall be a Moffat electrically heated Turbofan Proofer and Holding Cabinet ETL Listed and NSF-4 listed. The proofer and holding cabinet shall have double skin construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged and field reversible. Unit shall have capacity for up to 16 half size sheet pans or 8 full size sheet pans. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a mechanical thermostat and humidity via a control of the water tank. A thermometer shall indicate the cabinet temperature. Proofer and holding cabinet shall be mounted on castors, with two rigid castors at rear and two swivel castors dual swivel and wheel lock and front. Proofer and Holding Cabinets shall be fitted with NEMA 5-15P cordsets. Unit shall be supplied in 100% recyclable shipping packaging.

STANDARD FEATURES

- Full size sheet pan capacity
- 5 tray Oven / 8 tray Proofer
- Compact 28³/₈" / 735mm width
- Low unit height 61³/₈" / 1560mm
- Side hinged doors (standard LH hinge)
Optional RH hinge (field convertible)
- Dual halogen lamps in Oven and Proofer
- Proofer with dual function Proof and Holding modes

OVEN

- 3¹/₈" / 85mm tray spacing
- Digital display Time and Temperature Controls
- Large easy view 3/4" / 20mm high displays
- Electronic thermostat control
- Electronic timer with countdown or time count modes
- Manual mode and Program mode
- 20 programs with 3 stage cooking and stage end alarms
- Core Probe program cooking (optional Core Probe Kit)
- Moisture injection mode (5 levels) and manual injection
- 2 speed bi-directional reversing fan system
- Safe-Touch vented door
- Porcelain enameled oven chamber
- Plug-in continuous oven door seal
- 5 oven wire racks supplied
- 100% recyclable packaging

PROOFER

- 3" / 76mm tray spacing
- Auto water fill system with optional integrated water filter kit
- Continuous door seal
- Low velocity circulation fan system
- Mechanical thermostat and Humidity level control
- Cabinet temperature display thermometer
- 4 dia. 3" / 76mm castors with 2 front castors dual wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

ACCESSORIES

- Optional M236060 Core Temperature Probe Kit
- Optional 3M Cuno water filter kit complete with cartridge and connection fittings
- Installs in pre-fitted rear housing of cabinet for flush rear installation

E32D5 Full Size Digital / Electric Convection Oven

P8M Full Size Manual / Electric Proofer/Holding Cabinet

CONSTRUCTION - Oven (E32D5)
 Porcelain enameled fully welded oven chamber
 Stainless steel front, sides and top exterior
 Stainless steel frame side hinged door
 0.2" / 5mm thick door inner and outer glass
 Stainless steel control panel
 Aluminized coated steel base and rear panels

CONSTRUCTION - Proofer (P8M)
 304 stainless steel interior cabinet
 Stainless steel front, sides and top exterior
 Stainless steel interior side racks
 Stainless steel frame side hinged door
 0.2" / 5mm thick door glass
 Stainless steel control panel
 Aluminized coated steel base and rear panels

CONTROLS - Oven (E32D5)
 Electronic controls with Digital Time and Temperature display, Manual or Program modes
 Large ¾" / 20mm high LED displays
 Two individual time and temperature setting control knobs
 ON/OFF and Oven Lights key
 Fan LO speed key
 Timer Start/Stop key
 Moisture Injection key (5 levels)
 Programs select key
 Actual temperature display key
 Adjustable buzzer/alarm volume
 Thermostat range 150-500°F / 50-260°C
 Timer range from 180 minute in countdown mode / 999 minute in count-up mode
 Optional Core Probe temperature range 122-194°F / 50-90°C
 Over-temperature safety cut-out

CONTROLS - Proofer (P8M)
 Off / Proof / Holding mode selector switch
 Mechanical thermostat 32-185°F / 20-85°C
 Humidity level control
 Cabinet temperature thermometer
 Auto-fill water system standard

CLEANING
 Stainless steel top and side exterior panels
 Porcelain enameled oven chamber
 Fully removable stainless steel oven and proofer side racks
 Removable stainless steel oven fan baffle
 Easy clean door system with hinge out door inner glass (no tools required)
 Removable plug-in oven door seal (no tools required)

SPECIFICATIONS

Electrical Requirements
 Oven (E32D5)
 208V, 60Hz, 1-phase, 5.8kW, 28A
 220-240V, 50/60Hz, 1-phase, 6.5kW, 27A
 No cordset supplied

Proofer (P8M)
 110-120V, 50/60Hz, 1-phase, 1.45kW, 11.6A
 NEMA 5-15P cordset fitted

Water Requirements
 Cold water connection ¾" GHT male
 80psi maximum inlet pressure / 20psi minimum inlet pressure
 Connection to oven optional

External Dimensions
 Width 28 7/8" / 735mm
 Height 61 3/4" / 1560mm
 Depth 31 7/8" / 810mm

Nett Weight
 Oven (E32D5)
 196lbs / 89kg
 Proofer (P8M)
 171lbs / 77.5kg

Packing Data
 Oven (E32D5)
 231lbs / 105kg
 20.1ft³ / 0.57m³
 Width 29 7/8" / 760mm
 Height 32" / 815mm
 Depth 36 7/8" / 925mm

Proofer (P8M)
 210lbs / 95.3kg
 26.8 ft³ / 0.76m³
 Width 30" / 760mm
 Height 42 1/2" / 1080mm
 Depth 36 7/8" / 925mm

INSTALLATION CLEARANCES

Rear 2" / 50mm
 LH Side 2" / 50mm
 RH Side* 3" / 75mm
 * For fixed installations a minimum of 20" / 500mm is required for service

CLEARANCE FROM SOURCES OF HEAT


A minimum distance of 12" / 300mm from the appliance sides is required



www.moffatusa.com
 www.turbofanoven.com

U.S.A.

Moffat Inc
 3760 Industrial Drive, Suite B
 Winston-Salem
 NC 27105-2637
 Ph Toll Free 1-800-551 8795
 Ph 336-661 0257
 Fax 336-661 9546
 Email sales@moffat.com
 www.moffatusa.com



ISO9001
 Quality Management Standard

Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
 US.TFN.S.1701

an Ali Group Company



The Spirit of Excellence