

Cooling Rack Mobile

- Ideal for cooling, storing, transporting and merchandising baked goods.
- Extremely durable and easy to maneuver on four 5" polyurethane swivel stem casters.
- The frame is constructed of all welded 1" aluminum square tubing with removable nickel chrome plated steel wire shelving for easy cleaning.
- 11" spacing between shelves.

Model	Oudouina	Overall Dimensions							Capacity		Approx.	
Number	Ordering Number	Width		Length		Height		Capacity		Ship Wt		
- Number		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb) (kg)		(lb)	(kg)	
MCR-6	126068	25	635	49	1,245	6613/16	1,697	800	363	100	45	
Caster In	Caster Information											
757	123684	Swiv	Swivel Square Stem Caster with 5" Polyurethane Wheel									
7112	122180	5" P	5" Polyurethane Wheel									

Freight Class: 250

Equipment Guide

✓ LIFE WARRANTY

AGAINST RUST

MEDIUM DUTY USE

Equipment Guide

MEDIUM DUTY USE



- Perfect for fast-paced, busy operations.
- Ideally suited for both fried and frozen products in all stages of preparation.
- Heavy duty, all welded aluminum construction resists rust and corrosion.
- Supplied with removable, easy to clean, aluminum drip pan.
- Two handles facilitate Maneuvering easily on four 5" polyurethane plate casters. Four corner bumpers protect fixtures.

NAI - I	0.1		Ov	erall Di	Devley	Approx.					
Model Number	Ordering Number	Width		Length		Hei	ght	Basket Capacity	Ship Wt		
		(in)	(mm)	(in)	(mm)	(in)	(mm)	- Capacity	(lb)	(kg)	
FFR18	183513	18	457	271/4	692	52	1,333	18	20	9	
FFR27	183521	243/4	629		092	32		27	22	10	
Caster Info	Caster Information										
738A	128784	Swiv	Swivel Plate Caster with 5" Polyurethane Wheel								
7112	122180	5" Po	5" Polyurethane Wheel								

Freight Class: 250

Can Dispensing Rack, Gravity Fed - FIFO

- First In-First Out can rack automatically rotates your inventory. Organizes and maximizes your stockroom space.
- Replaces 14' of 18" x 4 tier wire shelving.
- Self feeding, gravity-fed shelves keeps stock rotated and fresh.
- Convenient front loading for easy stocking.
- Cans are visible and accessible for quick and easy inventory.
- Made of all welded, high strength, extruded aluminum.

Equipment Guide

- √ Best
- ✓ HEAVY DUTY USE
- ✓ LIFE WARRANTY
 AGAINST RUST



Model Number	Order#		0	verall [Dimens	(Can	Approx.			
		# Width		Length		Height		Capacity		Ship Wt	
		(in)	(mm)	(in)	(mm)	(in)	(mm)	#10	Runner Shelf	(lb)	(kg)
CR-156F	229121	27	686	44	1,118	76	1,930	156	13	85	39

Freight Class: 250





Self Feeding Keeps Inventory Rotated & Fresh!

FFR18

Can Dispensing Racks, Full Size

Equipment Guide

- √ Best
- √ HEAVY DUTY USE
- ✓ LIFE WARRANTY
 AGAINST RUST



- Organizes can stock and maximizes available space. Selffeeding feature keeps stock rotated.
- Vertical uprights and cross braces are constructed of 1½" aluminum tubing.
- Mobile units are easily maneuvered on two 5" locking swivel and two 5" rigid polyurethane plate casters.

Model		Type of	Overall Dimensions							Can		rox.
Number	Order#	Unit	Width		Length		Height		Capacity		Ship Wt	
			(in)	(mm)	(in)	(mm)	(in)	(mm)	#10	#5	(lb)	(kg)
CR-162 EXPRESS SHIP	112491	Stationary	251/4	641	35	889	71	1,803	162	216	60	27
CR-162AJ	112504	Adjustable										
CR-162M	112512	Mobile Station	271/2	699	35	889	76	1,930	162	216	66	30
Caster Information												
738A	128784	Swivel P	Swivel Plate Caster with 5" Polyurethane Wheel									
743A	128792	Rigid Pla	Rigid Plate Caster with 5" Polyurethane Wheel									
7112	122180	5" Polyur	ethan	e Whe	el							

Option for CR-162M: Specify options by adding suffix to Model Number CORR Correctional Package

Freight Class: 250

Can Mobile Dispensing Racks, Half Size

Equipment Guide

- √ Best
- √ HEAVY DUTY USE
- ✓ LIFE WARRANTY
 AGAINST RUST



- Organizes can stock and maximizes available space.
 Self-feeding feature keeps stock rotated.
- Vertical uprights and cross braces are constructed of 1½" aluminum tubing.
- Half size racks double as a work top. Available with stainless steel, aluminum, or poly-top work surfaces.
- Mobile units are easily maneuvered on two 5" locking swivel and two 5" rigid polyurethane plate casters.

				Ove	rall Di	Can Capacity		Approx. Ship Wt				
Model Number	Order#	Type of Top	Width		Length					Height		
		100	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10	#5	(lb)	(kg)
CR-54M	112521	Aluminum									50	23
CR-54PT	112547	Poly Top	271/2	699	35	889	35	889	54	72	65	29
CR-54SS	112555	Stainless Steel									42	19
CR-72M	112563	Aluminum		699	35	889	40	1,016	72	96	58	26
CR-72PT	112571	Poly Top	271/2								72	33
CR-72SS	112580	Stainless Steel									62	28
Caster In	Caster Information											
738A	128784	Swivel F	late C	aster v	vith 5"	Polyur	ethan	e Whe	el			
743A	128792	Rigid Pla	ate Ca	ster wi	th 5" F	olyure	thane	Wheel				
7112	122180	5" Polyu	rethan	e Whe	el							

Freight Class: 250







