



PRO SERIES 24" WAFER PLATE RANGES



IMPERIAL

MODEL NUMBERS:

IR-4-EW IR-4-EW-XB

IR-4-EW

Shown with optional casters and stub back

10" x 10" wafer heating elements heat up to 650°.



High performance 5.3 KW element provides even heating throughout the oven.

PLATE ELEMENTS

- 650° maximum termperature heats food up to 50% faster.
- 3.75 KW heating elements are 10" x 10" (254 x 254) for maximum pan contact.
- Features 12" x 12" (305 x 305) wafer plates in front, and 12" x 13" (305 x 330) in rear.
- Top design helps prevents spills from entering unit for easier clean-up.
- Thermostatic controlled plates

EXTERIOR FEATURES

- Stainless steel front, sides, backguard, shelf, landing ledge and kick plate.
- Welded and polished stainless steel seams.
- Large 3.25" (83 mm) stainless steel landing ledge
- 6" (152 mm) heavy duty legs with adjustable feet
- One year parts and labor warranty.

STANDARD OVEN

- Baffle above the element distributes heat flow to provide even cooking temperatures throughout the 5.3 KW oven. Splatter screen protects the element from spills.
- Chef depth oven interior accommodates standard 18" x 26" (457 x 660 mm) sheet pans front-to-back and side-by-side.
- Space Saver oven dimensions are 20"w x 26"d x 14"h (508 x 660 x 356)
- Heavy duty thermostat with temperature range from 150°F to 500°F (65°C to 260°C)
- Porcelainized sides, rear, deck and inner door liner.
- Side oven controls are protected from heat in an insulated side compartment
- Stamped inner door liner provides extra strength while improving heat retention.
- Splatter screen protects the element from spills.
- One chrome oven rack is included.












SPEC SERIES 24" WAFER PLATE RANGES







| MODEL | PLATE ELEMENTS | SHIP WEIGHT (KG) LBS | DIMENSIONS | CRATED DIMENSIONS |
|------------|-------------------|-------------------------|--|---|
| IR-4-EW | 4 | (234) 516 | 24"W x 35 7/8" D x 56 1/2"H (610 x 911 x 1435 mm) | 26.5" W x 39" D x 35" H (673 x 991 x 889 mm) |
| IR-4-EW-XB | 4 | (234) 516 | 24"W x 35 7/8" D x 56 1/2"H (610 x 911 x 1435 mm) | 26.5" W x 39" D x 35" H (673 x 991 x 889 mm) |

CLEARANCE REQUIREMENTS

For use only on non-combustible floors. Legs or casters are required for non-combustible floors; or 2" (51 mm) overhang is required when curb mounted. Provide 0" clearance from non-combustible surfaces and 6" (152 mm) from combustible surfaces.

ELECTRICAL REQUIREMENTS

| MODEL | TOTAL KW | VOLTS | PHASE | AMPS |
|------------|-------------|-------|-------|------|
| | 20.3 | 208 | 3 | 65 |
| IR-4-EW | | 240 | 3 | 57 |
| | | 480* | 3 | 29 |
| | 15.0 | 208 | 3 | 42 |
| IR-4-EW-XB | | 240 | 3 | 36 |
| | | 480* | 3 | 18 |

Notes: Measurements in () are metric equivalents.

Contact Imperial about additional single phase options.

OPTIONS AND ACCESSORIES

- 6" (152 mm) stainless steel stub back, in lieu of standard backguard
- 11" (279 mm) stainless steel stub back, in lieu of standard backguard
- Reinforcement channels for mounting cheesemelter or salamander
 Extra oven racks
- Griddle top
- 6" (152 mm) casters
- 480 volts, 3 phase







^{*}Additional charge