

A6500-K SPECIFICATIONS

Point of use water cooler

Model	A3500-K
Cold Water	0.6 GAL OF 50 / HR (2.3L OF 10°C)
Hot Water	1.8 GAL OF 185 / HR (7.0 OF 85 5°C)
Dimensions	10.7" (272MM) X 12.3" D (314MM) X 37.2" H (945MM)
Shipping Weight	35 LBS (15KG)
Cold Tank	3.3 LITER (STAINLESS STEEL)
Hot Tank	1.6 LITER (STAINLESS STEEL)
Stainless Steel Grade	SUS304

Cold and Hot water: The above rates tested in ambient temperature 90°F (32°C).
Water inlet temperature 80°F (27°C)

EXCLUSIVE FEATURES



Dual Float



Safety Hot Push Faucet



Hot Water Tank

CABINET

Top and front panels are molded of ABS plastic and side panels are made of electric zinc coated steel with high polymer polyester resin.

REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No Lubricant needed. Refrigerant is controlled by accurately calibrated cappillary tube.

DRIP TRAY

Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid diverts dripwater into receptacle.

HOT WATER

Water temperature is controlled to nearly 185°F (85°C) by automatic, on-off switch is easily accessible on the rear control panel.

FAUCETS

Durable polypropylene. Self-closing type. Easy to operate.

COLOR

Black and stainless steel

HOT WATER TANK

Hygienic type stainless steel. Highly efficient internal heating element. Fire proof insulation.

COLD WATER THERMOSTAT

Temperature is controlled to 4°C - 10°C by adjustable thermostat, easily accessible on back.

WARRANTY

One year blanket, 3 years on sealed compressor.

COLD WATER TANK

Hygienic stainless steel.



DRINKING WATER COOLER
LISTED
36NK

A6500-K

