

ABC DRY CHEMICAL



ABC or MULTI-PURPOSE extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface where it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.



B424
P/N 15267

B461
P/N 15386

B441
P/N 14966

423
P/N 01010

BRASS VALVE

RUGGED

- 6-Year manufacturer's warranty
- Stored-pressure design
- Dependable drawn-steel cylinders
- Durable high-gloss polyester powder paint
- All-metal valve construction

BRASS VALVE—Heavy Duty

- Chrome-plated brass valve body
- Stainless steel handle & lever

ALUMINUM VALVE—Light to Medium Duty

- Anodized aluminum valve body
- Anodized aluminum handle & lever

- Temperature range -65°F to 120°F

USER-FRIENDLY

- Easy and economical to maintain and service
- QR coded and multilingual labels OPTION
- USCG approved with bracket listed on UL label
- Chrome cylinders (see chart below)



B417T
P/N 15217

B500T
P/N 15310

B402T
P/N 15281

B443
P/N 15393

B456
P/N 14967

A411
P/N 11213

ALUMINUM VALVE



MANUFACTURED AND TESTED TO UL STANDARDS
COMPLIES WITH NFPA 10 STANDARD
ISO-9001/ISO-14001 CERTIFIED UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S504 - UL 299 &
CAN/ULC-S508 - UL 711

AVAILABLE IN WHEELED EXTINGUISHERS

LARGEST SELECTION OF EXTINGUISHER SIZES AND OPTIONS AVAILABLE

AGENT TYPE	ABC DRY CHEMICAL									
VALVE TYPE	Anodized Aluminum						Chrome-Plated Brass			
DESIGN	Nozzle	Hose & Nozzle					Hose & Nozzle			
MODEL NUMBER	B417T	B500/B500T	B402/B402T	B443	B456	A411	B424	B461	B441	423
UL & ULC RATING	1A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	10A:120B:C	2A:10B:C	3A:40B:C	4A:80B:C	10A:120B:C
CAPACITY (LBS.)	2.5	5	5	6	10	20	5	6	10	20
*SHIPPING WT. (LBS.)	5.25/5.5	9.25/9.5	9.25/9.5	12.75	18	36.5	10.5	14	19.5	38
HEIGHT (IN.)	15.25	15.25	15.25	16	20	24	15.5	16.25	20.5	24
WIDTH (IN.)	5.5	7.25	7.25	7.75	7.75	10.25	8	8.5	8.75	10.25
DEPTH (IN.)	3	4.25	4.25	5	5	7	4.25	5	5	7
RANGE (INITIAL- FT.)	9-15	12-18	12-18	15-21	15-21	15-21	12-18	15-21	15-21	15-21
DISCHARGE TIME (SEC.)	9	14	14	14.5	22	30	14	14	22	30
OPTIONAL CHROME CYLINDER	Yes	Yes	Yes		Yes			Yes	Yes	
NOMINAL OPERATING PRESSURE	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG
INCLUDED BRACKET	Vehicle	Wall/Vehicle			Wall		Wall			

*Shipping weight includes box.

