

Project	
Item #	
Quantity	

AF-50/25 TUBE FRYER

GAS TYPE:

NATURAL

LP



AF-50/25

STANDARD FEATURES

- All stainless steel front and sides
- (1) 50 lb. capacity stainless steel tank 14" \times 14" frying area
- (1) 25 lb. capacity stainless steel tank 6 3/4" \times 14" frying area
- Burners rated at 40,000 BTU/hr. each
- Special alloy metal diffuser located in the burner tube for better heat transfer
- Millivolt control system with 100% safety shut off
- Thermostatic control with 200°F to 400°F range
- 1-1/4" full port drain valve
- 6" legs or optional casters
- Three baskets with plastic coated handles
- Two year limited warranty, parts, and labor
- Five year limited (prorated) warranty on stainless steel tank

AVAILABLE OPTIONS

- Stainless steel tank cover
- Four casters front two with locking brakes
- Stainless Steel Splash Guard
- Quick disconnect and flexible gas hose
- Joiner Strip: Connects two fryers and prevents oil from getting in between the fryers or drain station



Model Shown AF-50/25

Shown with optional casters

DESCRIPTION

American Range, 50/25 pound fryer, Model AF-50/25. All stainless steel front and sides, with heavy gauge stainless steel tanks and rated at 40,000 BTU/hr. AF-50 fryer tube fryer equipped with 3 burners and a AF-25 fryers equipped with two burners. Unit has one 50 pound capacity tank and one 25 pound capacity tank. Includes three fry baskets with plastic coated handles. Standard Millivolt control system with 100% safety shut off and Thermostatic control with a temperature range of 200°F to 400°F. 1-1/4" full port drain valve for easy cleaning.












AF-50/25 TUBE FRYER







Shipping Weight*

MODEL	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BURNERS	COOKING AREA	BTU	(kW)	LBS	(KG)
AF-50/25	23 1/4" (591 mm	30-1/4" (768 mm)	45-3/4" (1162 mm)	5	(1) 14" x 14" (356 mm x 356 mm) (1) 8-3/4" x 14" (171 mm x 356 mm)	200,000	(59)	225	(102)

Specify type of gas and altitude if over 2000 feet. Please specify gas type when ordering.

MANIFOLD PRESSURE							
NATURAL GAS	PROPANE GAS	MANIFOLD SIZE					
5.0" W.C.	10.0" W.C.	3/4" (19MM)					

NMFCCODE: 25970-2 Class: 85

*Shipping weight includes packaging and is approximate.

American Range is a quality manufacturer of commercial cooking equipment. Due to continuing product improvements, these specifications are subject to change without prior notice.

COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2° (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0° . When unit is placed next to combustible walls, clearances must exceed 12° (305) from sides, and 4° (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment" (NOTE: For North America only)





