Item No.

The Anets Pasta Pro Is A Safe, Simple Way To Make Perfectly Cooked Pasta

Anets offers a safe, consistent and easy way to make traditional pasta. This self-contained system eliminates handling heavy pots and hot water. Quick, efficient heating system brings fresh water to a boil in less than 10 minutes. Super sensitive thermostat accurately controls the temperature from a soft simmer to a hard boil. Cook more than just pasta, blanch vegetables, boil seafood or reheat sauces in this all-purpose water cooker. Add features like a timer, and automatic lift to assure product consistency.. Attach a rinse station and faucet for a complete pasta station.

STANDARD FEATURES

- Cook pot is made of special marine grade stainless steel specifically for water applications
- Open vat design is easy to clean
- Unique cross fire burners provide a 4 sided heating system
- Special copper flashed heat exchangers transfer heat directly into the cookpot for maximum efficiency and instant recovery
- Super sensitive thermostat maintains water temperature within +/-1°F
- Built-in manual water-fill enables the operator to adjust water input for continuous refill. Manual water control eliminates the need for complicated floats and costly components
- Overflow area safeguards against accidental overfill
- Skimming area provides a place to continuously remove starch build up
- Front drain tray



GPC-14 adjustable continuous water fill, rinse station, hot and cold faucet, split bulk baskets and casters.











SPECIFICATIONS

- Model
- Certification
- **BTUH**
- Gas Pressure
- Gas Connection
- Electrical Requirements
 GPC-14
 GPC-14A
- Thermostat
- Temperature Range
- Burners
- Hi-Limit
- Safety Pilot
- Pulse Ignitor
- Cookpot
- Cabinet
- Water Capacity
- Water Drain Elbow

STANDARD ACCESSORIES

- Rack type basket support
- Front drain tray
- 6 Adjustable chrome plated legs

OPTIONS AND ACCESSORIES

- Adjoining rinse station (RSF14)
- Hot and cold water faucets
- Fully automatic single lift
- 15 minute timer with buzzer
- Batch and single portion baskets
- Low temperature thermostat for rethermalizing or blanching (160°F to 212°F) (71°C-100°C)
- 6 Casters

GPC-14, Basic

GPC-14A, Fully automatic single lift

CSA, NSF, ETL

111,000

NG 3.5 WC, LP 10 WC

3/4 NPT

120V, 60Hz, 1PH, 2Amps 120V, 60Hz, 1PH, 5Amps

Solid state

190°F to 212°F (88°C-100°C)

160°F to 212°F (71°C-100°C) (optional)

Atmospheric pre-mix

Safety control turns off main gas supply

at 250°F (121°C)

100% gas shut off valve

Battery Powered Ignitor

Marine grade stainless steel

Stainless steel


8.5 gallons

1-1/4" NPT Female Threads


NOTE: Baskets must be ordered separately

BASKETS


- Bulk
- Split bulk (Twin)
- 5^{3/4} Round
- Portion rack with
 (9) 10oz plastic
 portion cups



Top View



Side View



Warranty: 1 year Parts and Labor, 5 years Frypot Part only.