



BR700G

★★★★★ 4.7 (53) [Write a review](#)



Power ☐ 700VA ☐ 1000VA ☐ 1300VA ☐ 1500VA

Outlet Count ☐ 6 ☐ 8 ☐ 10

High Performance Computer and Electronics UPS for Premium Power Protection

Includes: USB cable, User Manual

Technical Specifications

Output

Max Configurable Power (Watts)	420Watts / 700VA
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Topology	Line Interactive
Waveform type	Stepped approximation to a sinewave
Transfer Time	8ms typical : 12ms maximum

Input

Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input voltage range for main operations	88 - 143V

Batteries & Runtime

Included Battery Modules	1
Typical recharge time	12hour(s)
Replacement Battery	RBC17 ↗
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	86
Runtime	View Runtime Graph View Runtime Chart
Efficiency	View Efficiency Graph

Communications & Management

Interface Port(s)	USB
-------------------	-----

Surge Protection and Filtering

Surge energy rating	354Joules
Data Line Protection	Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector), Coaxial cable for

CATV/SATV/modem/Audio-Video (coax connector)

Filtering

Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: instantaneous

Physical**Maximum Height** 7.48inches (190MM, 19.0CM)**Maximum Width** 3.58inches (91MM, 9.1CM)**Maximum Depth** 12.2inches (310MM, 31.0CM)**Net Weight** 15.73lbs. (7.15KG)**Shipping weight** 17.6lbs. (8.0KG)**Shipping Height** 9.92inches (252MM, 25.2CM)**Shipping Width** 5.43inches (138MM, 13.8CM)**Shipping Depth** 17.4inches (442MM, 44.2CM)**Color** Black**Master Carton Dimensions (Length x Width x Height)** 18inches (452MM)**Master Carton Units** 2.0**Master Carton Weight** 36.37lbs. (16.53)**Units per Pallet** 48.0**SCC Codes** 1073130426679 9**Environmental****Operating Temperature** 32 - 104 °F (0 - 40 °C)**Operating Relative Humidity** 0 - 95 %**Operating Elevation** 0-10000ft (0-3000meters)**Storage Temperature** -15 - 45 °C**Storage Relative Humidity** 0 - 95 %**Storage Elevation** 0-50000ft (0-15000meters)**Audible noise at 1 meter from surface of unit** 45.0dBA**Online thermal dissipation** 48.5BTU/hr**Conformance****Approvals** ENERGY STAR V2.0 (USA), FCC Part 15 Class B, NOM, TUV, UL 1778**Equipment protection policy** Lifetime : \$150000**Standard warranty** 3 years repair or replace**Sustainable Offer Status****RoHS** Compliant**REACH** REACH: Contains SVHCs**PEP** Available in Documentation tab**EOL** Available in Documentation tab**Proposition 65 Warning** Available in Documentation tab

