




500-1DN Drawer Warmer with feet



- Product moisture is retained without adding water.
- Digital control senses temperature drops faster, providing quick heat recovery time.



Short Form Spec

Alto-Shaam drawer warmer is constructed with a non-magnetic stainless steel exterior and removable stainless steel drawer rail supports. The drawer includes one (1) full-size (GN 1/1) 12" x 20" x 6" (305mm x 508mm x 152mm) stainless steel pan. The warmer is controlled by an ON/OFF power switch; up and down arrow buttons with a temperature range of 60°F to 200°F (16°C to 93°C); heat indicator light; temperature display button, and digital display.


☐ Model 500-1DN: One drawer warmer with feet, narrow design, non-vented drawer, 120V




Description	Part No.		
Arby's	202816		



Drawer Warmer with feet



	16-11/16" (423mm)
— 12-1/4" — (310mm)	
	Feet



$\textbf{Dimensions}\ \ H\ x\ W\ x\ D$

Exterior:

12-1/4" x 16-11/16" x 31-3/16" (310mm x 423mm x 792mm)

Pan size: 12" x 20" x 6" (305mm x 508mm x 152mm) GN 1/1

Electrical					
V	Ph	Hz	A	kW	
120	1	50/60	5.3	0.64	NEMA 5-15P 15A, 125V plug

Product Capacity

41 lbs (19 kg) maximum (34 baked potatoes, 50 dinner rolls)

Weight (est.)				
Net: 67 lb (30 kg)	Ship: 75 lb (34 kg)			
Carton dimensions: (L X W X H)				
33" x 21" x 15" (838mm x 533mm x 381mm)				

Clearance Requirement (for ventilation)

Minimum: 3" (76mm) at the back, 2" (51mm) at the top, and 1" (25mm) at both sides. On-site venting for proper airflow must also be provided for built-in counter installations.

Installation Requirements

Drawer warmer must be installed level, and must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. Phone: 262.251.3800 800.558.8744 U.S.A./Canada Fax: 262.251.7067 800.329.8744 U.S.A. only www.alto-shaam.com

