



Stainless design.  
Stellar performance.  
Superior value.

Project name: \_\_\_\_\_

Location: \_\_\_\_\_

Item #: \_\_\_\_\_ QTY: \_\_\_\_\_

Model #: \_\_\_\_\_

## ACP4SQ REFRIGERATOR

## COMPACT REFRIGERATED COUNTER-TOP PREP UNIT



### ACP4SQ

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full one year parts and labor warranty.
- ▶ Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- ▶ All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.



COMMERCIAL FREEZERS & REFRIGERATORS

Division of Broich Enterprises, Inc. 7550 Market Place Dr Eden Prairie, MN 55344  
952-941-2270 Fax: 952-941-3066 [www.arcticairco.com](http://www.arcticairco.com) [info@arcticairco.com](mailto:info@arcticairco.com)



# ACP4SQ

REFRIGERATOR

## COMPACT REFRIGERATED COUNTER-TOP PREP UNIT



Interior cabinet consists of full stainless steel liner.

Exterior cabinet consists of full stainless steel shell.

Plastic non-scratch feet included.

Self contained capillary tube system using environmentally friendly R600a Hydrocarbon gas.

Coldwall heat exchange system.

No on/off switch. Must be de-energized to defrost.

Includes 1/6 size Lexan pans and covers. 6" deep back row. 4" deep front row.

Optional legs — part #69438K. Set of four, 4" s/s legs.

► Tested to NSF Standard 7 requirements for open food storage.

► Standard with full one year parts and labor warranty.

► NOTE: No defrost systems. ACP is designated as an "in-service" item. Unit needs to be shut off to defrost.

### STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

| Model Number | External Dimensions |        |        | Temperature Range | Cord Length | Pans (1/6 size) | Pan Depth           | HP  | AMPS | REF   | NEMA Plug | Crate Weight |
|--------------|---------------------|--------|--------|-------------------|-------------|-----------------|---------------------|-----|------|-------|-----------|--------------|
| ACP4SQ       | 15"                 | 25.75" | 9.125" | 33°F to 41°F      | 6'          | 4               | Front 4"<br>Back 6" | 1/5 | 1.4  | R600a | 5-15P     | 65Lbs        |

