

Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

Victoria Arduino Athena Leva 3 Group Spec Sheet

Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3qpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Softening Equipment

- Water Softener Capacity: Single 4400 apa
- 2. Water Softener Capacity: Double 8800 gpg
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable
- 5. Water Softener Capacity: Manual 4400 gpg

Power Requirements

Volts: 220 (voltage range of 208-240)

Watts: 5000 Amp draw: 23

Receptacle: Nema L6-30 Twist









NSF / ANSI Std.4

The average water consumption of this machine is 4 gallons per day, which represents 128 drinks at 4oz per drink.

Water Softener/Maintenance Calculation

Cartridge Grain _ **Gallon Capacity** Davs Until Cartridge Water Hardness Gallons of Water Needs to be Replaced Capacity (grains per gallon) of Cartridge Used per Day

Counter Space Requirements

Height: 28 inches Depth: 22 inches

Width: 34 inches Weight: 185 pounds

Drain Requirements

Phone:

Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.

34" Countertop Drain Hole Location 22 (Front)

Shipping Dimensions & Weight

Height: 25 inches Depth: 25 inches

Width: 42 inches Weight: 205 pounds



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation.	
Customer Name:	Signature:
Company Name:	