





- STA1800
- STA2400
- STA4800

Specifications

Description: Robust steamers with high volume output. Automated steam allows for less training and a consistent end result. Key Feature: Automatic valve shuts off steam when programmed temperature is reached.	Standard Warranty: 2-year parts warranty and 1-year labor warranty from date of shipment. Covers parts (except wear & tear) to be free from manufacturer defect. Labor authorized through manufacturer. <i>See AstraMfr.com for more details.</i>
Construction & Performance: <ul style="list-style-type: none"> • 2 automatic temperature controlled steam valves • 1 manual hot water valve • All US standard hardware • Rotary Procon® Pump • Vacuum valve prevents milk from entering the boiler • Brass flare fittings for longevity 	Agency Listings: <ul style="list-style-type: none"> • UL STD 197 • CSA 222.2 No. 109 • ETL-Sanitation to NSF-4 <div style="display: flex; justify-content: space-around; align-items: center;">   </div>

Technical Information

Part Number	Power			Water	Boiler Capacity (L)	Dimensions In.			WGT LBS
	W	V	amps (req. circuit)			W	D	H	
STA1800	2000	110/220	20/20	Hookup	4.2	13	20.5	17	70
STA2400	2700	220	20	Hookup	4.2	13	20.5	17	70
STA4800	4800	220	30	Hookup	7	13	20.5	21	80

- 5' power cord
- For 110V, plug is NEMA 5-15
- No 220V plug, but provided if specified
- 50/60hz capable
- Water supply required: 30-50psi
- Inlet water line: 1/4" ID, 3/8" OD
- Drain line: 1/2" ID, 3/4" OD