

Item #: 178A12RHC Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco A-12R-HC 25" Solid Door Reach-In Refrigerator

Item #178A12RHC



Technical Data

Width	24 13/16 Inches
Depth	23 7/16 Inches
Height	63 3/8 Inches
Interior Width	20 7/8 Inches
Right Door Opening Width	20 7/8 Inches
Shelf Width	20 1/4 Inches
Interior Depth	18 7/8 Inches
Shelf Depth	17 11/16 Inches
Interior Height	48 3/8 Inches
Amps	3.1 Amps

Features

- 430 series stainless steel exterior and aluminum interior with 304 stainless steel floor
- Shorter height is great for tight spaces
- Includes 3 shelves with a 88 lb. capacity each
- Digital temperature controls for easy operation
- R-290 hydrocarbon refrigerant; 115V; 1/3 hp

Certifications



ETL, US



5-15P




ETL Sanitation

Technical Data

Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	317 Watts
Access Type	Doors
BTU (LBP)	850 BTU
Capacity	11.12 cu. ft.
Capacity (per Shelf)	88 lb.
Color	Silver
Compressor Location	Bottom Mounted
Construction	Stainless Steel and Aluminum
Door Style	Swing
Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors
Features	Removable Magnetic Door Gaskets
Handle Material	Plastic
Hinge Location	Right
Horsepower	1/3 hp
Installation Type	Freestanding
Number of Compressors	1 Compressor
Number of Doors	1 Doors
Number of Shelves	3 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	2.6 oz.
Refrigerant Type	R-290
Sections	1 Section
Starting Amps	9.3 Amps
Starting Wattage	951 Watts
Temperature Range	33 - 40 Degrees F
Type	Refrigerators

Plan View





Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco A-12R-HC 25" solid door refrigerator, you receive performance you can depend on! A painted aluminum interior with a 304 stainless steel floor gives you increased durability, while a 430 stainless steel door and exterior sides give it a sleek appearance. For convenience, this model comes with 3 epoxy coated shelves which can each hold up to 88 lb. of refrigerated product. Each shelf features shelf clips so you can customize the shelf locations to meet the needs of your business.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 1/3 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. It is also easier to reach for maintenance. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the stay open / locking door, automatic defrosting, and a digital temperature control with a digital display. This item requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.