

Item#:	178A23FHC		Project:	
Otv:		Date:		Approval:

Avantco A-23F-HC 29" Solid Door Reach-In Freezer

Item#178A23FHC







Technical Data

Width	29 Inches	
Depth	32 3/16 Inches	
Height	82 1/2 Inches	
Power Cord Length	96 Inches	
Interior Width	24 3/8 Inches	
Right Door Opening Width	24 5/16 Inches	
Shelf Width	23 1/4 Inches	
Interior Depth	27 1/8 Inches	
Shelf Depth	23 5/8 Inches	
Interior Height	53 1/2 Inches	

Features

- Corrosion-resistant stainless steel exterior and aluminum interior with 304 stainless steel floor
- Features a self-closing and stay-open locking door
- Includes 3 epoxy coated shelves with 88 lb. capacity each; 5" casters included
- Digital temperature controller with automatic defrost function
- R-290 refrigerant; 115V; 2/3 hp

Certifications



ETL, US



15P




ETL Sanitation



Technical Data

Amps	4.2 Amps	
Hertz	60 Hz	
Phase	1 Phase	
Voltage	115 Volts	
Wattage	396 Watts	
Access Type	Doors	
BTU (LBP)	2080 BTU	
Capacity	23.06 cu. ft.	
Capacity (per Shelf)	88 lb.	
Caster Size	5 Inches	
Casters	With Casters	
Color	Silver	
Compressor Location	Bottom Mounted	
Construction	Stainless Steel and Aluminum	
Door Style	Swing	
Door Type	Solid	
Dutch Half Doors	Without Dutch Half Doors	
Features	Removable Magnetic Door Gaskets	
Handle Material	Plastic	
Hinge Location	Right	
Horsepower	3/5 hp	
Installation Type	Freestanding	
Number of Doors	1 Doors	
Number of Shelves	3 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	4.1 oz.	
Refrigerant Type	R-290	
Sections	1 Section	
Starting Amps	12.6 Amps	
Starting Wattage	1188 Watts	
Temperature Range	-81 Degrees F	
Туре	Freezers	

Plan View





Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco A-23F-HC 29" solid door freezer, you receive performance you can depend on! A painted aluminum interior with a 304 stainless steel floor gives you increased durability, while a 430 stainless steel door and exterior sides give it a sleek appearance. For convenience, 3 epoxy coated shelves feature shelf clips for customization when desired.

Designed to maintain temperatures from -8 to -1 degree Fahrenheit, this freezer boasts a bottom-mounted 2/3 hp compressor that Uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the stay open locking door mechanism, automatic defrosting, and a digital temperature control with digital display. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.