

Item #: 178AWT60F Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco AWT-60F 60" Worktop Freezer with 3 1/2" Backsplash

Item #178AWT60F



Technical Data

| | |
|-------------------|----------------|
| Width | 60 3/16 Inches |
| Depth | 29 1/2 Inches |
| Height | 38 3/4 Inches |
| Power Cord Length | 7 Feet |
| Interior Width | 56 1/4 Inches |
| Shelf Width | 27 3/4 Inches |
| Interior Depth | 25 Inches |
| Shelf Depth | 22 3/16 Inches |
| Backsplash Height | 3 1/2 Inches |
| Interior Height | 26 1/8 Inches |

Features

- 430 type stainless steel exterior and aluminum interior with 304 type stainless steel floor
- Foamed-in-place polyurethane insulation increases energy efficiency
- Self-closing and stay-open door features for easy loading and unloading
- Features easy-to-use recessed handles for quick interior access
- Uses R-290 refrigerant; 115V, 2/3 hp

Certifications



ETL, US



5-15P



ETL Sanitation

Technical Data

| | |
|----------------------|--|
| Work Surface Height | 35 1/4 Inches |
| Amps | 4.5 Amps |
| Hertz | 60 Hz |
| Phase | 1 Phase |
| Voltage | 115 Volts |
| Wattage | 517.5 Watts |
| Access Type | Doors |
| Backsplash | With Backsplash |
| BTU (LBP) | 1991 BTU |
| Capacity | 18.51 cu. ft. |
| Capacity (per Shelf) | 66 lb. |
| Compressor Location | Rear Mounted |
| Compressor Style | Side / Rear Breathing |
| Construction | Stainless Steel and Aluminum |
| Door Style | Swing |
| Door Type | Solid |
| Features | Automatic Electric Defrost Casters Digital Temperature Controller Removable Magnetic Door Gaskets Self-Closing Doors Stay-Open Doors With Backsplash |
| Hinge Location | Left Right |
| Horsepower | 2/3 hp |
| Number of Doors | 2 Doors |
| Number of Shelves | 2 Shelves |
| Plug Type | NEMA 5-15P |
| Refrigerant Type | R-290 |
| Style | Counter Height |
| Temperature Range | -8 - 0 Degrees F |
| Type | Worktop Freezers |

Notes & Details

Make food preparation as convenient as possible with the Avantco 60" worktop freezer. With a spacious stainless steel worktop surface for slicing, dicing, assembling, mixing, and other food prep tasks, the unit features a 3 1/2" backsplash for wall protection and freezer storage space below. It is readily accessible through the doors, which open up to 2 shelves that help you organize your ingredients and best utilize the roomy interior. Plus, because each accommodates up to 66.14 lb., the included PVC-coated wire shelves are well equipped for holding heavy bulk ingredients, from frozen broccoli and cauliflower to frozen pork chops.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchens with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The painted aluminum interior with a 304 type stainless steel floor also offers the stability necessary for heavy, regular use. It comes with 4 reliable casters, 2 of which are braking casters, for easy mobility around your establishment.

This worktop freezer ensures optimal performance by operating with a 2/3 hp refrigeration system that circulates R-290 hydrocarbon refrigerant to maintain temperatures from -8 to 0 degrees Fahrenheit. R-290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation is CFC- and HCFC-free and helps to maintain interior temperatures.

Operation of the freezer is easy, thanks to a variety of special features, including an interior wall-mounted thermometer, auto-defrost, and pre-programmed digital controller. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area as needed. This worktop freezer requires a 115V electrical connection for operation and comes with a 7' power cord.



⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

Avantco Refrigeration