

| ltem#: | 178GDC40HCW |      | Project: |           |
|--------|-------------|------|----------|-----------|
| Otv:   |             | Date |          | Approval: |

# Avantco GDC-40-HC 48" White Customizable Swing Glass Door Merchandiser Refrigerator with LED Lighting

Item#178GDC40HCW







# **Technical Data**

| Width                       | 48 Inches       |  |
|-----------------------------|-----------------|--|
| Depth                       | 25 5/8 Inches   |  |
| Height                      | 84 5/8 Inches   |  |
| Power Cord Length           | 96 Inches       |  |
| Interior Width              | 43 5/16 Inches  |  |
| Left Door Opening<br>Width  | 19 11/16 Inches |  |
| Right Door Opening<br>Width | 19 11/16 Inches |  |
| Shelf Width                 | 21 1/4 Inches   |  |
| Interior Depth              | 21 5/16 Inches  |  |
| Shelf Depth                 | 18 11/16 Inches |  |

#### **Features**

- 2 self-closing, anti-fog dual-pane tempered glass swing doors with magnetic
- Interior LED lighting illuminates product; back lit exterior top panel attracts customers' attention
- 8 adjustable shelves with price tag strip on each shelf
- Easy to use digital temperature controls
- 115V; 1/2 hp; R-290 refrigerant

## **Certifications**











#### **Technical Data**

| Interior Height      | 46 7/16 Inches               |  |
|----------------------|------------------------------|--|
| Amps                 | 4.8 Amps                     |  |
| Hertz                | 60 Hz                        |  |
| Phase                | 1 Phase                      |  |
| Voltage              | 115 Volts                    |  |
| Wattage              | 518 Watts                    |  |
| Access Type          | Doors                        |  |
| BTU (LBP)            | 1331 BTU                     |  |
| Capacity             | 26.8 cu. ft.                 |  |
| Capacity (per Shelf) | 88 lb.                       |  |
| Color                | White                        |  |
| Compressor Location  | Bottom Mounted               |  |
| Door Style           | Swing                        |  |
| Door Type            | Glass                        |  |
| Features             | Customizable<br>LED Lighting |  |
| Hinge Location       | Left<br>Right                |  |
| Horsepower           | 1/2 hp                       |  |
| Installation Type    | Freestanding                 |  |
| Interior Color       | White                        |  |
| Number of Doors      | 2 Doors                      |  |
| Number of Shelves    | 8 Shelves                    |  |
| Refrigerant Capacity | 4.2 oz.                      |  |
| Refrigerant Type     | R-290                        |  |
| Sections             | 2 Sections                   |  |
| Starting Amps        | 14.4 Amps                    |  |
| Starting Wattage     | 1554 Watts                   |  |
| Temperature Range    | 33 - 40 Degrees F            |  |
| Туре                 | Merchandising Refrigeration  |  |

### **Notes & Details**

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-40-HC 48" white merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek finish. And, since the housing is made from white coated steel, you can be sure that it will provide superior durability. This unit boasts 2 anti-fogging, dual-pane tempered glass swing doors to ensure that customers always have a clear view of your products, while 8 epoxy coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate salads, wraps, or sandwiches. Interior LED lighting also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 1/2 hp compressor that runs on R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include self-closing aided by magnetic gaskets, automatic defrosting, as well as a digital temperature control and display. This item requires a 115V electrical connection for operation.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.