

# Avantco GDC-69-HC 78 1/4" Black Swing Glass Door Merchandiser Refrigerator with LED Lighting and Customizable Panel

Item #178GDC69BC



## Technical Data

Width	78 1/4 Inches
Depth	30 Inches
Height	84 13/16 Inches
Power Cord Length	84 Inches
Interior Width	73 1/2 Inches
Interior Depth	23 5/8 Inches
Interior Height	55 1/8 Inches
Amps	10.7 Amps
Hertz	60 Hz
Phase	1 Phase

## Features

- 3 self-closing, anti-fog swing glass doors
- Temperature range: 33 to 40 degrees Fahrenheit
- R290 refrigerant
- Interior LED lighting
- 115V, 4/5 hp

## Certifications



5-15P



ETL, US




Customizable

## Technical Data

Voltage	115 Volts
Access Type	Doors
BTU (LBP)	2010 BTU
Capacity	57.5 cu. ft.
Capacity (per Shelf)	90 lb.
Color	Black
Compressor Location	Bottom Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable LED Lighting
Hinge Location	Left Right
Horsepower	4/5 hp
Installation Type	Freestanding
Interior Color	White
Number of Doors	3 Doors
Number of Shelves	12 Shelves
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Sections	3 Sections
Temperature Range	33 - 40 Degrees F
Type	Merchandising Refrigeration

## Plan View



## Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-69-HC 78 1/4" black merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek finish. And, since the housing is made from black coated steel, you can be sure that it will provide superior durability. This unit boasts three an anti-fogging glass swing doors to ensure that customers always have a clear view of your products, while (12) epoxy coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate salads, wraps, or sandwiches. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 4/5 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the doors, automatic defrosting, and a digital temperature control. This item requires a 115V electrical connection for operation.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).