



Item #: 178GDS33WC Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco GDS-33-HCW 40" White Sliding Glass Door Merchandiser Refrigerator with LED Lighting and Customizable Panel

Item #178GDS33WC



Technical Data

Width	40 Inches
Depth	30 Inches
Height	83 7/8 Inches
Power Cord Length	96 Inches
Amps	1.91 Amps
Voltage	120 Volts
Access Type	Doors
BTU (LBP)	1264 BTU
Capacity	33.5 cu. ft.
Capacity (per Shelf)	90 lb.

Features

- Features (2) sliding glass doors to provide easy access and eliminate the need for space to open
- Interior LED lighting illuminates product ;back lit exterior top panel attracts customers' attention
- Narrow design takes up less space while offering plenty of storage
- Easy-to-read digital temperature controls
- 120V; 1/2 hp; R290 refrigerant; 1.91 Amps

Certifications



5-15P



ETL, US




Customizable

Technical Data

Color	White
Compressor Location	Bottom Mounted
Display Case Type	Refrigerated
Door Style	Sliding
Door Type	Glass
Features	Customizable LED Lighting Lighted Interior Self-Closing Doors
Horsepower	1/2 hp
Interior Color	White
Number of Doors	2 Doors
Number of Shelves	8 Shelves
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Sections	2 Sections
Temperature Range	33 - 40 Degrees F
Type	Merchandising Refrigeration

Plan View



Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDS-33-HCW 40" white merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek white finish and a lighted top graphics area. And, since the housing is made from coated steel, you can be sure that it will provide superior durability. The unit's narrow design helps to minimize its footprint, allowing you to better utilize your available space.

Additionally, it boasts anti-fogging glass sliding doors to ensure that customers always have a clear view of your products, while (8) plastic-coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate changing inventory and menus. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 1/2 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the door, automatic defrosting, and a digital temperature control. This item requires a 120V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.