

Item#:	178HBB25HC		Project:	
Otv.		Date:		Annroval:

Avantco HBB-25-HC 25" Black Horizontal Bottle Cooler

Item #178HBB25HC







Technical Data

Width	26 3/8 Inches	
Depth	28 Inches	
Height	34 1/4 Inches	
Power Cord Length	90 Inches	
Interior Width	22 1/4 Inches	
Interior Depth	23 Inches	
Interior Height	15 3/4 Inches	
Amps	1.1 Amps	
Hertz	60 Hertz	
Phase	1 Phase	

Features

- R290 hydrocarbon refrigerant
- Spacious 4.1 cu. ft. interior
- Includes a locking lid and a removable bottle opener / cap catcher
- Easy-to-read digital temperature controller and auto-defrost function
- 115V; 1/4 hp; 1.1 Amps

Certifications



ETL Sanitation 5-15P ETL, US






Technical Data

Voltage	115 Volts	
Access Type	Doors	
BTU (LBP)	666 BTU	
Capacity	4.1 cu. ft.	
Compressor Location	Bottom Mounted	
Compressor Style	Side / Rear Breathing	
Construction	Aluminum Steel	
Exterior Finish	Black	
Horsepower	1/4 HP	
Lid Style	Sliding	
Lid Type	Solid	
Number of 12 oz. Bottles	104 Bottles	
Number of 12 oz. Cans	156 Cans	
Number of Lids	1 Lid	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	2.8 oz.	
Refrigerant Type	R-290	
Temperature Range	33 - 40 Degrees F	

Plan View





Notes & Details

Keep bottles of beer or soda on hand at all times by storing them in this Avantco HBB-25-HC 25" bottle cooler! Maintaining temperatures from 33 to 40 degrees, the cooler provides 4.1 cu. ft. of interior storage to ensure that a wide supply of bottles are kept cold and ready for thirsty customers. For your utmost convenience, a bottle opener / cap catcher is included with the unit. Just grab a beer, use the opener, and serve!

This unit is designed for outstanding durability to ensure that it withstands service through even your busiest days and nights. It features a black epoxy-coated steel exterior and a painted aluminum interior. A stainless steel lid opens and closes with ease, making for easy drink retrieval. Because it locks, the lid also secures your beverage selection, making sure that your supply is always safe.

This cooler guarantees optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. Plus, the foamed-in-place polyurethane insulation adds rigidity and promotes proper temperatures. This ensures that all beverages held in the unit are at the perfect serving temperature.

You can adjust the cooler with the digital temperature controller as needed, and maintain the unit with its auto-defrost function. This unit requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.