

Item #: 178SS1FHC Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco SS-1F-HC 29" Stainless Steel Solid Door Reach-In Freezer

Item #178SS1FHC



Technical Data

Width	29 Inches
Depth	32 3/16 Inches
Height	82 1/2 Inches
Power Cord Length	96 Inches
Interior Width	24 3/8 Inches
Right Door Opening Width	24 5/16 Inches
Shelf Width	20 7/8 Inches
Interior Depth	27 1/8 Inches
Shelf Depth	25 3/16 Inches
Interior Height	60 1/4 Inches

Features

- Corrosion-resistant stainless steel exterior and interior with LED lighting
- Features 1 self-closing, stay-open, locking door with full length stainless steel handle
- Perforated interior rear air duct for better air flow
- Removable one-piece grill for easy cleaning and service
- R290 refrigerant; 115V; 2/3 hp

Certifications



ETL, US



5-15P




ETL Sanitation

Technical Data

Amps	4.2 Amps
Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Wattage	396 Watts
Access Type	Doors
BTU (LBP)	2080 BTU
Capacity	23.06 cu. ft.
Casters	With Casters
Color	Silver
Compressor Location	Bottom Mounted
Construction	All Stainless Steel
Door Style	Swing
Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors
Features	LED Lighting Removable Magnetic Door Gaskets Self-Closing Doors
Handle Material	Stainless Steel
Hinge Location	Right
Horsepower	2/3 HP
Individual Shelf Capacity	100 lb.
Installation Type	Freestanding
Number of Doors	1 Doors
Number of Shelves	3 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	4.1 oz.
Refrigerant Type	R-290
Sections	1 Section
Starting Amps	12.6 Amps
Starting Wattage	1188 Watts
Temperature Range	-8 - -1 Degrees F
Type	Freezers

Plan View





Notes & Details

Providing impressive performance and dependable durability, this Avantco SS-1F-HC 29" stainless steel solid door reach-in freezer is engineered to hold your frozen food investments in a food safe environment. Designed with a 430 stainless steel door and exterior sides, the unit features a sleek appearance that's matched with its ability to withstand busy, heavy-use kitchens. Plus, the interior is 304 stainless steel, giving the unit superior corrosion resistance and cleanability; it won't become damaged by inevitable spills and messes. As a result, it's easier for your employees to maintain during the hustle and bustle of their daily tasks. For ultimate storage flexibility, this freezer even comes with 3 epoxy coated shelves with a versatile shelf slide design that can accept full size food pans! Designed for your utmost convenience, the unit is sure to accommodate your ever-evolving needs as your business grows, expands, and transforms over time. This unit also boasts interior LED lighting that automatically turns on and off when you open and close the door. This helps improve visibility and streamline your work flow. For long-lasting quality assurance and peace of mind, this unit also comes with a 2 year Parts and Labor Warranty.

Programmed to maintain temperatures from -8 to -1 degree Fahrenheit, this freezer ensures that all frozen food products are held in a proper, food safe environment to preserve their quality and integrity. To help achieve this, the robust, bottom-mounted 2/3 hp compressor runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For maximum structural rigidity, the entire cabinet is foamed-in place using polyurethane insulation.

Making the freezer easy to monitor and operate, an automatic defrost feature and a digital temperature control with digital display are integrated for intuitive use. The solid door includes a self-closing mechanism, which enables easy access at all times. A set of casters are included for easy mobility during cleaning. This item requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.