

| Item#: | 178SSUC27FHC | | Project: | | |
|--------|--------------|-------|----------|-----------|--|
| Otv. | | Date: | | Approval: | |

Avantco SS-UC-27F-HC 27" Undercounter Freezer

Item #178SSUC27FHC







Technical Data

| Width | 27 Inches | |
|-----------------------------|---------------|--|
| Depth | 29 1/2 Inches | |
| Height | 35 1/4 Inches | |
| Power Cord Length | 84 Inches | |
| Interior Width | 22 1/4 Inches | |
| Right Door Opening Width | 22 1/4 Inches | |
| Interior Depth | 22 7/8 Inches | |
| Interior Height | 23 1/2 Inches | |
| Work Surface Height | 35 1/4 Inches | |
| Amps | 3.6 Amps | |

Features

- Strong and sleek 430 type stainless steel exterior
- 304 type stainless steel interior maintains temperatures from -8 to -1 degrees
- Foamed-in-place polyurethane insulation
- Easy-to-read digital temperature controller and auto-defrost function
- 115V; 1/3 hp

Certifications



ETL, US






ETL Sanitation



Technical Data

| Hertz | 60 Hz | |
|----------------------|-----------------------------------|--|
| Phase | 1 Phase | |
| Voltage | 115 Volts | |
| Wattage | 235 Watts | |
| Access Type | Doors | |
| BTU (LBP) | 881 BTU | |
| Capacity | 5.5 cu. ft. | |
| Capacity (per Shelf) | 88 lb. | |
| Compressor Location | Rear Mounted | |
| Compressor Style | Side / Rear Breathing | |
| Door Style | Swing | |
| Door Type | Solid | |
| Features | Removable Magnetic Door Gaskets | |
| Hinge Location | Right | |
| Horsepower | 1/3 hp | |
| Number of Doors | 1 Doors | |
| Number of Shelves | 1 Shelf | |
| Plug Type | NEMA 5-15P | |
| Refrigerant Capacity | 2.3 oz. | |
| Refrigerant Type | R-290 | |
| Starting Amps | 10.8 Amps | |
| Starting Wattage | 705 Watts | |
| Style | Counter Height | |
| Temperature Range | -81 Degrees F | |
| Top Capacity | 441 lb. | |
| Туре | Freezers Undercounter Freezers | |

Plan View





Notes & Details

Make cold food storage as convenient as possible with the Avantco 27" undercounter refrigerator. With a spacious refrigerated portion readily accessible through its door, the unit opens up to a shelf to help you organize your ingredients and best utilize the 5.5 cu. ft. interior. Plus, because it accommodates up to 88 lb., the epoxy-coated steel shelf is well equipped for holding heavy bulk ingredients, from dozens of eggs to jars of condiments and sauces.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint.

This refrigerator ensures optimal performance by operating with a 1/3 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to add rigidity to the body's structure.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. $2\ 1/2$ " casters make moving simple for easy cleaning and bring the unit to an ADA-compliant working height. This undercounter unit requires a 115V electrical connection for operation.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.