

Item#:	178SSUC27RHC		Project:	
Otv <sup>.</sup>		Date:		Approval:

## Avantco SS-UC-27R-HC 27" Undercounter Refrigerator

Item #178SSUC27RHC







#### **Technical Data**

Width	27 Inches
Depth	29 1/2 Inches
Height	35 1/4 Inches
Power Cord Length	84 Inches
Interior Width	22 1/4 Inches
Right Door Opening Width	22 1/4 Inches
Interior Depth	22 7/8 Inches
Interior Height	23 1/2 Inches
Work Surface Height	35 1/4 Inches
Amps	1.1 Amps

#### **Features**

- Strong and sleek 430 type stainless steel exterior
- 304 type stainless steel interior maintains temperatures from 33 to 40 degrees
- Foamed-in-place polyurethane insulation
- Casters for easy mobility
- 115V; 1/4 hp; 1.1 Amps

#### Certifications





ETL Sanitation







# **Technical Data**

Hertz	60 Hertz	
Phase	1 Phase	
Voltage	115 Volts	
Access Type	Doors	
BTU (LBP)	666 BTU	
Capacity	5.5 cu. ft.	
Compressor Location	Rear Mounted	
Compressor Style	Side / Rear Breathing	
Door Style	Swing	
Door Type	Solid	
Features	Removable Magnetic Door Gaskets Self-Closing Doors	
Hinge Location	Right	
Horsepower	1/4 HP	
Individual Shelf Capacity	88 lb.	
Number of Doors	1 Doors	
Number of Shelves	1 Shelf	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	2.8 oz.	
Refrigerant Type	R-290	
Style	Counter Height	
Temperature Range	33 - 40 Degrees F	
Top Capacity	441 lb.	
Туре	Refrigerators Undercounter Refrigerators	





### **Plan View**





**TOP VIEW** 







#### **Notes & Details**

Make cold food storage as convenient as possible with the Avantco 27" undercounter refrigerator. With a spacious refrigerated portion readily accessible through its door, the unit opens up to a shelf to help you organize your ingredients and best utilize the 5.5 cu. ft. interior. Plus, because it accommodates up to 88 lb., the epoxy-coated steel shelf is well equipped for holding heavy bulk ingredients, from dozens of eggs to jars of condiments and sauces.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint.

This refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to add rigidity to the body's structure.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This undercounter unit requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.