

## Avantco SS-UC-36F-HC 36" Undercounter Freezer

Item #178SSUC36FHC



### Technical Data

Width	36 1/4 Inches
Depth	29 1/2 Inches
Height	35 Inches
Power Cord Length	84 Inches
Interior Width	33 Inches
Left Door Opening Width	14 5/16 Inches
Right Door Opening Width	14 5/16 Inches
Interior Depth	22 7/8 Inches
Interior Height	23 1/2 Inches
Work Surface Height	35 1/4 Inches

### Features

- Strong and sleek type 430 stainless steel exterior
- Type 304 stainless steel interior maintains temperatures from -8 to -1 degrees Fahrenheit
- Foamed-in-place polyurethane insulation
- Easy-to-read digital temperature controller
- 115V; 1/2 hp

### Certifications



5-15P



ETL, US




ETL Sanitation

## Technical Data

Amps	4.1 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	275 Watts
Access Type	Doors
BTU (LBP)	1264 BTU
Capacity	8.2 cu. ft.
Capacity (per Shelf)	88 lb.
Compressor Location	Rear Mounted
Compressor Style	Side / Rear Breathing
Door Style	Swing
Door Type	Solid
Features	Removable Magnetic Door Gaskets
Hinge Location	Left Right
Horsepower	1/2 hp
Number of Doors	2 Doors
Number of Shelves	2 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	3.2 oz.
Refrigerant Type	R-290
Starting Amps	12.3 Amps
Starting Wattage	825 Watts
Style	Counter Height
Temperature Range	-8 - -1 Degrees F
Top Capacity	441 lb.
Type	Freezers Undercounter Freezers

## Plan View



1785SUC36FHC



## Notes & Details

Make cold food storage as convenient as possible with the Avantco 35 1/4" undercounter refrigerator. With a spacious refrigerated portion readily accessible through its two doors, the unit opens up to two shelves to help you organize your ingredients and best utilize the interior space. Plus, because each accommodate up to 88 lb., the epoxy-coated steel shelves are well equipped for holding heavy bulk ingredients, from dozens of eggs to jars of condiments and sauces.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a type 430 stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with type 304 stainless steel, also offers the durability necessary for heavy, regular use. Because of its low, undercounter design, the unit can effortlessly add refrigerated storage space without requiring space devoted solely to its footprint. This unit also comes with a 2 year Parts and Labor Warranty, providing lasting quality assurance and peace of mind.

This refrigerator ensures optimal performance by operating with a 1/2 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to add rigidity to the body's structure.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. 2 1/2" casters make moving simple for easy cleaning and bring the unit to an ADA-compliant working height. This undercounter unit requires a 115V electrical connection for operation.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).