



Item #: 178SSUD1RA Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco SS-UD-1RA 44" Stainless Steel Two Drawer Extra Deep Undercounter Refrigerator

Item #178SSUD1RA



Technical Data

| | |
|-------------------|----------------|
| Width | 44 1/2 Inches |
| Depth | 31 1/2 Inches |
| Height | 34 7/16 Inches |
| Power Cord Length | 98 Inches |
| Interior Width | 22 1/4 Inches |
| Packaging Width | 47 1/4 Inches |
| Interior Depth | 26 3/16 Inches |
| Packaging Depth | 34 1/4 Inches |
| Interior Height | 22 7/8 Inches |
| Packaging Height | 36 1/4 Inches |

Features

- Side-mounted compressor allows for greater storage depth
- Easy-to-read digital temperature controller
- Includes 2 easy-open drawers and 6 divider bars to hold full size or fractional pans
- Strong and sleek type 430 stainless steel exterior with type 304 stainless steel interior
- 115V; 1/3 hp

Certifications



ETL Sanitation



5-15P



ETL, US

| | |
|-----------------------------|---|
| Work Surface Height | 35 1/4 Inches |
| Amps | 4 Amps |
| Hertz | 60 Hz |
| Phase | 1 Phase |
| Voltage | 115 Volts |
| Wattage | 348 Watts |
| Access Type | Drawers |
| BTU (LBP) | 501 BTU |
| Capacity | 7.6 cu. ft. |
| Compressor Style | Side / Rear Breathing |
| Door Type | Solid |
| Features | Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets |
| Horsepower | 1/3 HP |
| Individual Shelf Capacity | 90 lb. |
| Insulation Material | Polyurethane Foam |
| Material | Stainless Steel |
| Maximum Ambient Temperature | 90 Degrees F |
| Net Weight | 176 lb. |
| Number of Drawers | 2 Drawers |
| Plug Type | NEMA 5-15P |
| Refrigerant Type | R-290 |
| Starting Amps | 12 Amps |
| Starting Wattage | 1044 Watts |
| Style | Counter Height |
| Temperature Range | 33 - 40 Degrees F |
| Top Capacity | 353 lb. |
| Type | Refrigerators Undercounter Refrigerators |

[illegible]

© 2024 Avantco Refrigeration



Notes & Details

Make cold food storage as convenient as possible with the Avantco SS-UD-1RA 44" extra deep undercounter two drawer refrigerator. With a spacious refrigerated portion readily accessible through easy sliding drawers, the unit opens up to 7.6 cu. ft. of refrigerated food storage. Plus, 6 divider bars are included. These fit in the drawers where they act as braces for full size or fractional pans. Reconfigure or remove the braces to best suit your inventory. Drawers provide excellent organization for your food pans and can help maximize your kitchen's workflow. Drawers also allow you to quickly pull ingredients for faster operation and ease of use.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint.

This refrigerator ensures optimal performance by operating with a 1/3 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to trap in the cold air and to prevent the ambient air from entering. This ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers. The side-mounted compressor allows for greater depth of storage over rear-mounted units.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This undercounter unit requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.