

Item #: 178SSUD3RK		Project:	
Otv:	Date:		Approval:

Avantco 93" Stainless Steel Extra Deep Undercounter Refrigerator with 4 **Left Drawers and 1 Door**

Item#178SSUD3RK





Technical Data

Width	93 13/16 Inches
Depth	31 1/2 Inches
Height	34 7/16 Inches
Power Cord Length	98 Inches
Interior Width	73 1/4 Inches
Packaging Width	96 9/16 Inches
Shelf Width	23.149999618530273 Inches
Interior Depth	26 3/16 Inches
Packaging Depth	34 1/4 Inches
Shelf Depth	24 2/5 Inches

Features

- Strong and sleek type 430 stainless steel exterior with type 304 stainless steel
- Side mounted compressor and digital temperature controller allow for greater depth of storage
- Cabinet section can accept full size bun pans
- Includes 4 left-side drawers and 12 divider bars to fit full size and fractional pans
- 115V; 1/4 hp

Certifications





ETL Sanitation 5-15P







Technical Data

Interior Height	22 7/8 Inches	
Packaging Height	36 1/4 Inches	
Work Surface Height	35 1/4 Inches	
Amps	5.7 Amps	
Hertz	60 Hz	
Phase	1 Phase	
Voltage	115 Volts	
Wattage	524 Watts	
Access Type	Doors and Drawers	
BTU (LBP)	809 BTU	
Capacity	25.4 cu. ft.	
Capacity (per Shelf)	90 lb.	
Compressor Style	Side / Rear Breathing	
Door Style	Swing	
Door Type	Solid	
Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets Self-Closing Doors Stay-Open Doors	
Hinge Location	Right	
Horsepower	1/4 hp	
Insulation Material	Polyurethane Foam	
Material	Stainless Steel	
Material Maximum Ambient Temperature	Stainless Steel 90 Degrees F	
Maximum Ambient Temperature	90 Degrees F	
Maximum Ambient Temperature Net Weight	90 Degrees F 342 lb.	
Maximum Ambient Temperature Net Weight Number of Doors	90 Degrees F 342 lb. 1 Doors	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers	90 Degrees F 342 lb. 1 Doors 4 Drawers	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P R-290	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Sections	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P R-290 3 Sections	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Sections Starting Amps	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P R-290 3 Sections 17.1 Amps	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Sections Starting Amps Starting Wattage	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P R-290 3 Sections 17.1 Amps 1572 Watts	
Maximum Ambient Temperature Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Sections Starting Amps Starting Wattage Style	90 Degrees F 342 lb. 1 Doors 4 Drawers 1 Shelf NEMA 5-15P R-290 3 Sections 17.1 Amps 1572 Watts Counter Height	



Plan View





Notes & Details

Make cold food storage as convenient as possible with the Avantco 93" extra deep undercounter refrigerator. With a spacious refrigerated portion readily accessible through 4 drawers on the left and 1 door on the right, the 25.4 cu. ft. unit helps you organize your ingredients. While the door section features an epoxy-coated shelf, the drawers include a total of 12 divider bars. These fit in the drawers where they act as braces for full size or fractional pans. Easily reconfigure or remove the braces to best suit your inventory.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint.

This refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to trap in the cold air and to prevent the ambient air from entering. This ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers. The sidemounted compressor allows for greater depth of storage over rear-mounted units.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This undercounter unit requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.