

Item #:	1/8SSWD1RA		Project:	
Otv.		Date:		Annroyal:

Avantco 44" Stainless Steel Two Drawer Extra Deep Worktop Refrigerator with 3 1/2" Backsplash

Item#178SSWD1RA







Technical Data

Width	44 1/2 Inches	
Depth	31 1/2 Inches	
Height	38 Inches	
Power Cord Length	98 Inches	
Interior Width	22 1/4 Inches	
Packaging Width	47 1/4 Inches	
Shelf Width	23.149999618530273 Inches	
Depth with Door Open	55 1/16 Inches	
Interior Depth	26 3/16 Inches	
Packaging Depth	34 1/4 Inches	

Features

- Strong and sleek type 430 stainless steel exterior with type 304 stainless steel
- Foamed-in-place polyure than e insulation maintains temperatures from $33\,\mathrm{to}\,40$ degrees Fahrenheit
- 3 1/2" backsplash for wall protection
- Includes 2 easy-open drawers and 6 divider bars
- 115V; 1/3 hp
- Note: only the worktop refrigerator holds the ETL certification

Certifications





ETL Sanitation




ETL, US



Technical Data

Shelf Depth	24 2/5 Inches
Interior Height	22 7/8 Inches
Packaging Height	39 Inches
Work Surface Height	35 1/4 Inches
Amps	4 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	348 Watts
Access Type	Drawers
BTU (LBP)	501 BTU
Capacity	7.6 cu. ft.
Capacity (per Shelf)	90 lb.
Compressor Style	Front / Rear Breathing
n -	6 11 1
Door Type	Solid
Poor Type Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash
	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets
Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash
Features Horsepower	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp
Features Horsepower Insulation Material	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam
Features Horsepower Insulation Material Material	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel
Features Horsepower Insulation Material Material Maximum Ambient Temperature	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb.
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of Drawers	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb. 2 Drawers
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of Drawers Plug Type	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb. 2 Drawers NEMA 5-15P
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of Drawers Plug Type Refrigerant Type	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb. 2 Drawers NEMA 5-15P R-290
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of Drawers Plug Type Refrigerant Type Starting Amps	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb. 2 Drawers NEMA 5-15P R-290 12 Amps
Features Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of Drawers Plug Type Refrigerant Type Starting Amps Starting Wattage	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash 1/3 hp Polyurethane Foam Stainless Steel 90 Degrees F 176 lb. 2 Drawers NEMA 5-15P R-290 12 Amps 1044 Watts

Plan View





Notes & Details

Make food preparation as convenient as possible with the Avantco SSWDR1 44" worktop refrigerator. With a spacious stainless steel worktop surface for slicing, dicing, assembling, mixing, and other food prep tasks, the unit features a $3\,1/2$ " backsplash for wall protection and a refrigerated storage space below. The refrigerated portion is readily accessible through the two doors, which open up to two shelves to help you organize your ingredients and best utilize the spacious interior. Plus, because they each accommodate up to 90 lb., the epoxy-coated steel shelves are well equipped for holding heavy bulk ingredients, from fresh produce to sauces, glazes, and other specialty condiments and garnishes.

This refrigerated unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use.

This worktop refrigerator ensures optimal performance by operating with a 1/3 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to trap in the cold air and to prevent the ambient air from entering. This ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers!

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This worktop refrigerator requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.