© 2025 Avantco Refrigeration	

Avantco Refrigeration

Qty: _____ Date: _____ Approval: _____

Avantco 93" Stainless Steel Extra Deep Worktop Refrigerator with 3 1/2" Backsplash with 2 Right Drawers and 2 Doors

Item #178SSWD3RE



Technical Data

Width	93 13/16 Inches
Depth	31 1/2 Inches
Height	38 Inches
Power Cord Length	98 Inches
Interior Width	73 1/4 Inches
Packaging Width	96 9/16 Inches
Shelf Width	23.149999618530273 Inches
Depth with Door Open	55 1/16 Inches
Interior Depth	26 3/16 Inches
Packaging Depth	34 1/4 Inches

Features

- Strong and sleek type 430 stainless steel exterior with type 304 stainless steel • interior
- Foamed-in-place polyure thane insulation maintains temperatures from 33 to 40 • degrees Fahrenheit
- 3 1/2" backsplash for wall protection •

AUNTO

- Includes 2 right-side drawers, 2 doors, and 6 divider bars •
- 115V; 1/4 hp •

Certifications














Тес	hnica	l Data

Shelf Depth	24 2/5 Inches
•	22 7/8 Inches
Interior Height	39 Inches
Packaging Height	
Work Surface Height	35 1/4 Inches
Amps	5.7 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	524 Watts
Access Type	Doors and Drawers
BTU (LBP)	631 BTU
Capacity	25.4 cu. ft.
Capacity (per Shelf)	90 lb.
Compressor Style	Front / Rear Breathing
Door Style	Swing
Door Type	Solid
Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets With Backsplash
Hinge Location	Left
Horsepower	1/4 hp
Insulation Material	Polyurethane Foam
Material	
	Stainless Steel
Maximum Ambient Temperature	90 Degrees F
Maximum Ambient Temperature Net Weight	
	90 Degrees F
Net Weight	90 Degrees F 342 lb.
Net Weight Number of Doors	90 Degrees F 342 lb. 2 Doors
Net Weight Number of Doors Number of Drawers	90 Degrees F 342 lb. 2 Doors 2 Drawers
Net Weight Number of Doors Number of Drawers Number of Shelves	90 Degrees F 342 lb. 2 Doors 2 Drawers 1 Shelf
Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type	90 Degrees F 342 lb. 2 Doors 2 Drawers 1 Shelf NEMA 5-15P
Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type	90 Degrees F 342 lb. 2 Doors 2 Drawers 1 Shelf NEMA 5-15P R-290
Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Starting Amps	90 Degrees F 342 lb. 2 Doors 2 Drawers 1 Shelf NEMA 5-15P R-290 17.1 Amps
Net Weight Number of Doors Number of Drawers Number of Shelves Plug Type Refrigerant Type Starting Amps Starting Wattage	90 Degrees F 342 lb. 2 Doors 2 Drawers 1 Shelf NEMA 5-15P R-290 17.1 Amps 1572 Watts

Plan View





Notes & Details

Make food preparation as convenient as possible with the Avantco 93" extra deep worktop refrigerator. With a spacious stainless steel worktop surface for slicing, dicing, assembling, mixing, and other food prep tasks, the unit features a 3 1/2" backsplash for wall protection and a refrigerated storage space below. The refrigerated portion is readily accessible through 2 drawers in the middle and 1 door on either side. These doors each open to an epoxy-coated steel shelf to help organize product. Drawers provide excellent organization for your food pans and can help maximize your kitchen's workflow. Drawers also allow you to quickly pull ingredients for faster operation and ease of use. Plus, 6 divider bars are included, which fit in the drawers where they act as braces for full size or fractional pans. Reconfigure or remove the braces to best suit your inventory. Providing 25.4 cu. ft. of space in total, the refrigerator makes it easy to store fresh produce, condiments, and a range of other ingredients needed for the prep station.

This refrigerated unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use.

This worktop refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to trap in the cold air and to prevent the ambient air from entering. This ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers!

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This worktop refrigerator requires a 115V electrical connection for operation.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.