

ltem#:	178UBB2GHCS		Project:	
Otve		Date:		Approval:

Avantco UBB-2G-HC 59" Stainless Steel Counter Height Glass Door Back Bar Refrigerator with LED Lighting

Item#178UBB2GHCS







Technical Data

Width	58 7/8 Inches
Depth	29 1/8 Inches
Height	36 1/4 Inches
Power Cord Length	106 Inches
Interior Width	46 1/4 Inches
Left Door Opening Width	21 1/2 Inches
Packaging Width	61 1/4 Inches
Right Door Opening Width	21 1/2 Inches
Shelf Width	22 1/2 Inches
Interior Depth	21 7/8 Inches

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 size kegs
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup and mainte
- Uses R290 refrigerant; 3/7 hp; 115V

Certifications







ETL Sanitation




Technical Data

Nominal Depth	Standard
Packaging Depth	30 1/2 Inches
Shelf Depth	21 1/2 Inches
Interior Height	30 1/2 Inches
Packaging Height	41 3/4 Inches
Amps	3.5 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	325 Watts
Access Type	Doors
BTU (LBP)	974 BTU
Capacity	(2) 1/2 Kegs 19.4 cu. ft.
Capacity (per Shelf)	88 lb.
Casters	Without Casters
Compressor Location	Side Mounted
Countertop Type	Stainless Steel
Door Style	Swing
Door Type	Glass
Exterior Finish	Stainless Steel
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets
Horsepower	3/7 hp
Insulation Material	Polyurethane Foam
Material	Stainless Steel
Maximum Ambient Temperature	90 Degrees F
Net Weight	258 lb.
Number of 12 oz. Bottles	288 Bottles
Number of 12 oz. Cans	256 Cans
Number of Doors	2 Danier
	2 Doors
Number of Kegs	2 Kegs
Number of Kegs Number of Shelves	
	2 Kegs
Number of Shelves	2 Kegs 4 Shelves
Number of Shelves Plug Type	2 Kegs 4 Shelves NEMA 5-15P
Number of Shelves Plug Type Refrigerant Capacity	2 Kegs 4 Shelves NEMA 5-15P 2.5 oz.
Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type	2 Kegs 4 Shelves NEMA 5-15P 2.5 oz. R-290
Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material	2 Kegs 4 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel
Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps	2 Kegs 4 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps
Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage	2 Kegs 4 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps 975 Watts



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-378-G-HC-S 59" counter height back bar refrigerator! Providing 19.4 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses four epoxy-coated shelves that each accommodate up to 88 lb. The interior is illuminated by bright LED lighting for optimal product visibility. The plastic-coated steel shelves are perfect for storing and organizing drinks for your bar service, from bottles of ale to bottles of cider.

The interior, made of strong 304 type stainless steel, is accessible through two glass doors. Because they're made of glass, the doors provide excellent product visibility, enabling you to easily view your current drink or ingredient selection for efficient drink preparation. For overall durability, the unit's exterior is made with stainless steel and is topped with a type 304 stainless steel work surface.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R-290 hydrocarbon refrigerant to maintain temperatures from 33-41 degrees Fahrenheit. R-290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.