

Item#:	178UBB378GS		Project:	
Otv:		Date:		Approval

Avantco UBB-378-G-HC-S 79" Stainless Steel Counter Height Glass Door **Back Bar Refrigerator with LED Lighting**

Item #178UBB378GS







Technical Data

Width	78 15/16 Inches
Depth	27 3/4 Inches
Height	36 1/4 Inches
Power Cord Length	96 Inches
Interior Width	66 3/8 Inches
Left Door Opening Width	20 1/4 Inches
Middle Door Opening Width	19 3/16 Inches
Packaging Width	80 11/16 Inches
Right Door Opening Width	20 1/4 Inches
Shelf Width	21 5/8 Inches

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and exterior
- LED interior lighting and glass doors to show off beverage selection
- Six adjustable epoxy-coated steel shelves can be removed to fit four 1/2 kegs
- Preprogrammed digital temperature controls with auto-defrost function for easy setup and maintenance
- 115V; 1/2 hp; R-290 refrigerant; 2.4 Amps

Certifications







ETL Sanitation




Technical Data

Depth with Door Open	48 9/16 Inches
Interior Depth	217/8 Inches
Nominal Depth	Standard
Packaging Depth	30 5/16 Inches
Shelf Depth	21 1/4 Inches
Interior Height	30 1/2 Inches
Packaging Height	41 3/4 Inches
Amps	2.4 Amps
Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Access Type	Doors
BTU (LBP)	1285 BTU
Capacity	(4) 1/2 Kegs 25.8 cu. ft.
Casters	Without Casters
Compressor Location	Side Mounted
Compressor Style	Side / Rear Breathing
Countertop Type	Stainless Steel
Door Style	Swing
Door Type	Glass
Exterior Finish	Stainless Steel
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting
Features Horsepower	Digital Temperature Controller Food Rated
	Digital Temperature Controller Food Rated LED Lighting
Horsepower	Digital Temperature Controller Food Rated LED Lighting 1/2 HP
Horsepower Individual Shelf Capacity	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb.
Horsepower Individual Shelf Capacity Insulation Material	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam
Horsepower Individual Shelf Capacity Insulation Material Material	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb.
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz.
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 1/2 Barrel 33 - 41 Degrees F
Horsepower Individual Shelf Capacity Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Style	Digital Temperature Controller Food Rated LED Lighting 1/2 HP 88 lb. Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 1/2 Barrel



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-3G-HC 69" stainless steel counter height glass door back bar refrigerator! Providing 23.4 cu. ft. of interior storage space, the unit comes with six shelves that accommodate up to 88 lb. each or (4) 1/2 kegs total. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, since the unit is rated to safely store food products, it provides versatility and helps you maximize the space you have available.

The interior, made of strong 304 type stainless steel, is accessible through two glass doors. Because they're made of glass, the doors provide excellent product visibility, enabling you to easily view your current drink or ingredient selection for efficient drink preparation. For overall durability, the unit's exterior is made with stainless steel and is topped with a type 304 stainless steel surface.

This back bar refrigerator ensures optimal performance by operating with a 1/2 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all products held in the unit remain at cool temperatures and are ready for immediate service to customers!

Delivering ease of use and maintenance, the refrigerator is easy to adjust with a digital temperature controller and features automatic defrost. Overall, the unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.