

Item #: 178UBB48HCS Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco UBB-48-HC-S 48" Stainless Steel Counter Height Narrow Solid Door Back Bar Refrigerator with LED Lighting

Item #178UBB48HCS



Technical Data

| | |
|--------------------------|----------------|
| Width | 48 3/4 Inches |
| Depth | 24 7/16 Inches |
| Height | 36 1/4 Inches |
| Power Cord Length | 106 Inches |
| Interior Width | 36 1/4 Inches |
| Left Door Opening Width | 16 7/16 Inches |
| Packaging Width | 51 1/4 Inches |
| Right Door Opening Width | 16 7/16 Inches |
| Shelf Width | 17 5/8 Inches |
| Interior Depth | 18 1/2 Inches |

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup and mainte
- 115V; 3/7 hp; R290 refrigerant

Certifications



ETL, US



5-15P




ETL Sanitation

Technical Data

| | |
|-----------------------------|---|
| Nominal Depth | Narrow |
| Packaging Depth | 27 1/2 Inches |
| Shelf Depth | 18 1/8 Inches |
| Interior Height | 30 1/2 Inches |
| Packaging Height | 41 3/4 Inches |
| Amps | 3.5 Amps |
| Hertz | 60 Hz |
| Phase | 1 Phase |
| Voltage | 115 Volts |
| Wattage | 325 Watts |
| Access Type | Doors |
| BTU (LBP) | 974 BTU |
| Capacity | (2) 1/2 Kegs 13 cu. ft. |
| Capacity (per Shelf) | 88 lb. |
| Casters | Without Casters |
| Compressor Location | Side Mounted |
| Countertop Type | Stainless Steel |
| Door Style | Swing |
| Door Type | Solid |
| Exterior Finish | Stainless Steel |
| Features | Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets |
| Horsepower | 3/7 hp |
| Insulation Material | Polyurethane Foam |
| Material | Stainless Steel |
| Maximum Ambient Temperature | 90 Degrees F |
| Net Weight | 231 lb. |
| Number of 12 oz. Bottles | 196 Bottles |
| Number of 12 oz. Cans | 144 Cans |
| Number of Doors | 2 Doors |
| Number of Kegs | 2 Kegs |
| Number of Shelves | 4 Shelves |
| Plug Type | NEMA 5-15P |
| Refrigerant Capacity | 2.5 oz. |
| Refrigerant Type | R-290 |
| Shelf Material | Epoxy-Coated Steel |
| Starting Amps | 10.5 Amps |
| Starting Wattage | 975 Watts |
| Temperature Range | 33 - 40 Degrees F |
| Top Capacity | 353 lb. |
| Top Type | Counter Height |

Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-48S-HC 48" stainless steel counter height narrow sliding glass door back bar refrigerator with LED lighting! Conveniently store a variety of bottles behind the bar so that they're ready to serve at all times, and gain 13 cu. ft. of refrigerated storage space for your most popular brews, ales, ciders, and other beverages. Its narrow design makes it more compact than similar units, making it ideal for operations that are tight on space.

Providing 13 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses (4) 17 5/8" x 18 1/8" shelves that each accommodate up to 88 lb. The epoxy-coated steel shelves in this food-rated unit are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale and beer to fresh fruit for mixed drinks and garnishes. The interior, made of strong 304 type stainless steel, is accessible through two sliding glass doors, taking up less precious space behind the bar and making it easy to grab drinks and garnishes quickly. This unit features easy-to-use digital temperature controls to make setting and changing the temperature simple. In addition, this refrigerator has interior LED lighting to maximize product visibility. Even if your bar area is dimly lit, bartenders and servers will have no trouble finding the drinks and garnishes they need. For overall durability, the unit's exterior is made with sleek stainless steel and is topped with a type 304 stainless steel surface.. The stainless steel top of this cooler can double as a garnish cutting and drink preparation space.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation helps to maintain internal temperatures and adds rigidity to the body's structure. This unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.