


ltem#:	178UBB48SGT		Project:	
Otv:		Date:		Approval:

Avantco UBB-48S-GT 48" Black Underbar Height Narrow Sliding Glass Door Back Bar Refrigerator with Galvanized Top and LED Lighting

Item #178UBB48SGT







Technical Data

Width	48 3/4 Inches	
Depth	24 7/16 Inches	
Height	34 1/4 Inches	
Power Cord Length	106 Inches	
Interior Width	36 1/4 Inches	
Left Door Opening Width	16 Inches	
Packaging Width	51 1/4 Inches	
Right Door Opening Width	16 Inches	
Shelf Width	17 5/8 Inches	
Interior Depth	18 1/2 Inches	

Features

- Galvanized steel top with stainless steel interior and black coated steel exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Glass doors and bright, LED lighting ensure easy product visibility and retrieval
- 115V; 3/7 hp; 2 Amps; R290 refrigerant

Certifications



5-15P





ETL Sanitation




Technical Data

Nominal Depth	Narrow	
Packaging Depth	27 1/2 Inches	
Shelf Depth	18 1/8 Inches	
Interior Height	29 Inches	
Packaging Height	41 3/4 Inches	
Amps	2 Amps	
Hertz	60 Hertz	
Phase	1 Phase	
Voltage	115 Volts	
Access Type	Doors	
BTU (LBP)	974 BTU	
Capacity	(2) 1/2 Kegs 13 cu. ft.	
Casters	Without Casters	
Compressor Location	Side Mounted	
Countertop Type	Galvanized Steel	
Door Style	Sliding	
Door Type	Glass	
Exterior Finish	Black	
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting	
Horsepower	3/7 HP	
Individual Shelf Capacity	88 lb.	
Insulation Material	Polyurethane Foam	
Material	Black Coated Steel / Stainless Steel	
Maximum Ambient Temperature	90 Degrees F	
Net Weight	231 lb.	
Number of 12 oz. Bottles	196 Bottles	
Number of 12 oz. Cans	144 Cans	
Number of Doors	2 Doors	
Number of Kegs	2 Kegs	
Number of Shelves	4 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	2.5 oz.	
Refrigerant Type	R-290	
Shelf Material	Epoxy-Coated Steel	
Temperature Range	33 - 40 Degrees F	
Top Capacity	353 lb.	
Тор Туре	Below Counter	



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-48S-GT 48" black underbar height narrow sliding glass door back bar refrigerator with LED lighting! Conveniently store a variety of bottles behind the bar so that they're ready to serve at all times, and gain 13 cu. ft. of refrigerated storage space for your most popular brews, ales, ciders, and other beverages. Its narrow design makes it more compact than similar units, making it ideal for operations that are tight on space.

The galvanized top design is ideal for low height, built-in bars with existing cabinetry. Providing 13 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses (4) 17 5/8" x 18 1/8" shelves that each accommodate up to 88 lb. The epoxy-coated steel shelves in this food-rated unit are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale and beer to fresh fruit for mixed drinks and garnishes. The interior, made of strong 201 type stainless steel, is accessible through two sliding glass doors, taking up less precious space behind the bar and making it easy to grab drinks and garnishes quickly. This unit features easy-to-use digital temperature controls to make setting and changing the temperature simple. In addition, this refrigerator has interior LED lighting to maximize product visibility. Even if your bar area is dimly lit, bartenders and servers will have no trouble finding the drinks and garnishes they need. For overall durability, the unit's exterior is made with black coated steel.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33-40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation helps to maintain internal temperatures and adds rigidity to the body's structure. This unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.