

Item #: 178UBB60GTG Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco UBB-60-GT-G 60" Black Underbar Height Narrow Glass Door Back Bar Refrigerator with Galvanized Top and LED Lighting

Item #178UBB60GTG



Technical Data

Width	60 3/4 Inches
Depth	24 7/16 Inches
Height	34 1/4 Inches
Power Cord Length	106 Inches
Interior Width	48 1/4 Inches
Left Door Opening Width	22 3/8 Inches
Packaging Width	63 1/2 Inches
Right Door Opening Width	22 3/8 Inches
Shelf Width	23 5/8 Inches
Interior Depth	18 1/2 Inches

Features

- Galvanized steel top with stainless steel interior and black coated steel exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Glass door and bright, LED lighting ensure easy product visibility and retrieval
- 115V; 3/7 hp; R290 refrigerant

Certifications



ETL, US



5-15P




ETL Sanitation



Technical Data

Nominal Depth	Narrow
Packaging Depth	27 1/2 Inches
Shelf Depth	18 1/8 Inches
Interior Height	29 Inches
Packaging Height	41 3/4 Inches
Amps	3.5 Amps
Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Wattage	325 Watts
Access Type	Doors
BTU (LBP)	974 BTU
Capacity	(2) 1/2 Kegs 17.3 cu. ft.
Casters	Without Casters
Compressor Location	Side Mounted
Countertop Type	Galvanized Steel
Door Style	Swing
Door Type	Glass
Exterior Finish	Black
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets
Horsepower	3/7 HP
Individual Shelf Capacity	88 lb.
Insulation Material	Polyurethane Foam
Material	Black Coated Steel / Stainless Steel
Maximum Ambient Temperature	90 Degrees F
Net Weight	276 lb.
Number of 12 oz. Bottles	252 Bottles
Number of 12 oz. Cans	192 Cans
Number of Doors	2 Doors
Number of Kegs	2 Kegs
Number of Shelves	4 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	2.5 oz.
Refrigerant Type	R-290
Shelf Material	Epoxy-Coated Steel
Starting Amps	10.5 Amps
Starting Wattage	975 Watts
Temperature Range	33 - 40 Degrees F
Top Capacity	353 lb.
Top Type	Below Counter

Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-60-GT-G 60" back bar refrigerator! Providing 17.3 cu. ft. of interior storage space, the unit houses 4 epoxy-coated steel shelves that accommodate up to 88 lb. each. The epoxy-coated steel shelves are perfect for storing and organizing drinks for your bar service, from bottles of ale to bottles of cider.

The galvanized top design is ideal for low height, built-in bars with existing cabinetry. The interior, made of strong 201 type stainless steel, is accessible through 2 glass doors. Because it's made of glass, the door provides excellent product visibility, enabling you to easily view your current drink or ingredient selection for efficient drink preparation. For overall durability, the unit's exterior is made with black coated steel.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33-40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.