Item #: 178UBB60GTGS Project: _____

© 2024 Avantco Refrigeration

Qty: _____ Date: _____ Approval: _____

Avantco UBB-60-GT-G-S 60" Stainless Steel Underbar Height Narrow Glass Door Back Bar Refrigerator with Galvanized Top and LED Lighting

Item #178UBB60GTGS

REFRIGERATION





Technical Data

Width	60 3/4 Inches	
Depth	24 7/16 Inches	
Height	34 1/4 Inches	
Power Cord Length	106 Inches	
Interior Width	48 1/4 Inches	
Left Door Opening Width	22 3/8 Inches	
Packaging Width	63 1/2 Inches	
Right Door Opening Width	22 3/8 Inches	
Shelf Width	23 5/8 Inches	
Interior Depth	18 1/2 Inches	

Features

- Galvanized steel top with stainless steel interior and stainless steel exterior •
- LED interior lighting •
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Glass door and bright, LED lighting ensure easy product visibility and retrieval •
- 115V; 3/7 hp; R290 refrigerant

Certifications



🕕 etl, US ـ


ETL Sanitation



Nominal Depth	Narrow	
	27 1/2 Inches	
Packaging Depth	18 1/8 Inches	
Shelf Depth	29 Inches	
Interior Height	41 3/4 Inches	
Packaging Height		
Amps	3.5 Amps	
Hertz	60 Hertz	
Phase	1 Phase	
Voltage	115 Volts	
Wattage	325 Watts	
Access Type	Doors	
BTU (LBP)	974 BTU	
Capacity	(2) 1/2 Kegs 17.3 cu. ft.	
Casters	Without Casters	
Compressor Location	Side Mounted	
Countertop Type	Galvanized Steel	
Door Style	Swing	
Door Type	Glass	
Exterior Finish	Stainless Steel	
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets	
Horsepower	1/2 HP	
Individual Shelf Capacity	88 lb.	
Insulation Material	Polyurethane Foam	
Material	Stainless Steel	
Maximum Ambient Temperature	90 Degrees F	
Net Weight	276 lb.	
Number of 12 oz. Bottles	252 Bottles	
Number of 12 oz. Cans	192 Cans	
Number of Doors	2 Doors	
Number of Kegs	2 Kegs	
Number of Shelves	4 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	2.5 oz.	
Refrigerant Type	R-290	
Shelf Material	Epoxy-Coated Steel	
Starting Amps	10.5 Amps	
Starting Wattage	975 Watts	
Temperature Range	33 - 40 Degrees F	
Top Capacity	353 lb.	
Тор Туре	Below Counter	







Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-60-HC-S 60" counter height narrow back bar refrigerator! Providing 17.3 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses four shelves that each accommodate up to 88 lb. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, with a narrow depth design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 201 type stainless steel, is accessible through two solid doors. For overall durability, the unit's exterior is made with sleek stainless steel and is topped with a type 304 stainless steel surface. This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling. This unit also comes with a 2 year Parts and Labor Warranty for long-lasting quality assurance and peace of mind.

A WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.