

ltem#:	178UBB72GHCS		Project:	
O+v.		Date		Approvale

Avantco UBB-72G-HC-S 73" Stainless Steel Counter Height Narrow Glass **Door Back Bar Refrigerator with LED Lighting**

Item #178UBB72GHCS







Technical Data


Width	72 3/4 Inches
Depth	25 3/4 Inches
Height	36 1/4 Inches
Power Cord Length	106 Inches
Interior Width	60 1/8 Inches
Left Door Opening Width	17 13/16 Inches
Middle Door Opening Width	17 13/16 Inches
Packaging Width	75 1/4 Inches
Right Door Opening Width	17 13/16 Inches
Shelf Width	19 - 20 1/2 Inches

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and exterior
- LED interior lighting
- Six adjustable epoxy-coated steel shelves can be removed to fit three 1/2 kegs
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup and mainte
- 115V; 3/7 hp; R290 refrigerant

Certifications







ETL Sanitation




Technical Data

Interior Depth	18 1/2 Inches
Nominal Depth	Narrow
Packaging Depth	27 1/2 Inches
Shelf Depth	19 - 20 1/2 Inches
Interior Height	30 1/2 Inches
Packaging Height	41 3/4 Inches
Amps	3.5 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	325 Watts
Access Type	Doors
BTU (LBP)	974 BTU
Capacity	(3) 1/2 Kegs 21.6 cu. ft.
Capacity (per Shelf)	88 lb.
Casters	Without Casters
Compressor Location	Side Mounted
Countertop Type	Stainless Steel
Door Style	Swing
Door Type	Glass
Exterior Finish	Stainless Steel
	Automatic Electric Defrost
Features	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets
Features Horsepower	Digital Temperature Controller Food Rated LED Lighting
	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets
Horsepower	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp
Horsepower Insulation Material	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam
Horsepower Insulation Material Material	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel
Horsepower Insulation Material Material Maximum Ambient Temperature	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb.
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz.
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps 975 Watts 33 - 40 Degrees F
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage	Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets 3/7 hp Polyurethane Foam Stainless Steel 90 Degrees F 331 lb. 308 Bottles 252 Cans 3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps 975 Watts



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-72G-HC-S 73" counter height narrow back bar refrigerator! Providing 21.6 cu. ft. of interior storage space, the unit fits up to (3) 1/2 kegs while housing six shelves that each accommodate up to 88 lb. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, with a narrow depth design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 304 type stainless steel, is accessible through three glass doors. Because they're made of glass, the doors provide excellent product visibility, enabling you to easily view your current drink or ingredient selection for efficient drink preparation. For overall durability, the unit's exterior is made of steel and is topped with a type 304 stainless steel surface.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.