

Item #:	178Z1F2A		Project:		
Qty:		Date:		Approval:	

Avantco Z1-F2-A 29" Solid Half Door Stainless Steel Reach-In Freezer

Item #178Z1F2A







Technical Data

Width	29 Inches		
Depth	32 3/16 Inches		
Height	81 11/16 Inches		
Interior Width	24 3/8 Inches		
Right Door Opening Width	24 5/16 Inches		
Interior Depth	27 1/8 Inches		
Interior Height	56 11/16 Inches		
Amps	3.6 Amps		
Hertz	60 Hertz		
Phase	1 Phase		

Features

- Corrosion-resistant stainless steel interior and exterior
- Features self-closing and stay-open locking solid doors
- Interior features full-size food pan slides and a perforated rear plenum
- Cabinet and maintenance alarms will sound and display on Carel iJ controller
- R-290 refrigerant; 115V; 2/3 hp; 3.6 Amps; 3 Year Parts and Labor

Certifications











Technical Data

Voltage	115 Volts		
Wattage	360 Watts		
Access Type	Doors		
Capacity	21.68 cu. ft.		
Casters	With Casters		
Color	Silver		
Compressor Location	Top Mounted		
Construction	All Stainless Steel		
Door Style	Swing		
Door Type	Solid		
Dutch Half Doors	With Dutch Half Doors		
Features	Automatic Electric Defrost Digital Display Electronic Controller Energy Star Qualified Removable Magnetic Door Gaskets Self-Closing Doors		
Hinge Location	Right		
Horsepower	2/3 HP		
Individual Shelf Capacity	88 lb.		
Installation Type	Freestanding		
Number of Doors	2 Doors		
Number of Shelves	3 Shelves		
Plug Type	NEMA 5-15P		
Refrigerant Capacity	2.6 oz.		
Refrigerant Type	R-290		
Sections	1 Section		
Temperature Range	-7 - 0 Degrees F		
Туре	Freezers		

Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco Z1-F2-A 29" solid half door stainless steel reach-in freezer, you receive performance you can depend on! A corrosion-resistant, all-stainless steel interior and exterior construction provides increased durability and a sleek appearance. The self-closing and stay-open locking solid doors give your staff the ability to more quickly and easily load your freezer when you get a delivery. Plus, a door open alarm alerts users to when the doors have been open for too long to keep your inventory safe and fresh.

This model features 3 plastic-coated steel shelves that fit in the freezer's pan slides. These slides fit full-size food pans (sold separately) and hold 33% more weight than shelf clips to make loading and unloading a breeze! The full-length U-shaped door handles further expedite the loading process. Since this model has half doors, you're able to keep other food cold if you're only opening half of the refrigerated space at a time. Thanks to the rear air duct, this model has exceptional air circulation. Included casters allow users to easily move and clean under the unit.

Designed to maintain temperatures from -7-0 degrees Fahrenheit, this freezer boasts a top-mounted 2/3 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit; meaning it'll get less dirty and won't be accidentally kicked. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller, automatic defrosting, and digital temperature control with digital display. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.