

Item#:	178Z2F4K		Project:	
O+v."		Data		Approval

Avantco Z2-F4-K 54" Solid Half Door Stainless Steel Reach-In Freezer

Item #178Z2F4K







Technical Data

Width	54 Inches	
Depth	32 3/16 Inches	
Height	81 11/16 Inches	
Interior Width	49 3/8 Inches	
Left Door Opening Width	22 9/16 Inches	
Right Door Opening Width	22 9/16 Inches	
Interior Depth	27 1/8 Inches	
Interior Height	56 11/16 Inches	
Amps	7.2 Amps	
Hertz	60 Hertz	

Features

- Corrosion-resistant stainless steel interior and exterior
- Features self-closing and stay-open locking solid doors
- Interior features full-size food pan slides and a perforated rear plenum
- Cabinet and maintenance alarms will sound and display on Carel iJ controller
- R-290 refrigerant; 1 2/7 hp; 7.2 Amps; 3 Year Parts and Labor

Certifications







ETL, US ETL Sanitation 5-15P Energy Star Qualified



Technical Data

Phase	1 Phase	
Voltage	115 Volts	
Wattage	720 Watts	
Access Type	Doors	
Capacity	43.93 cu. ft.	
Casters	With Casters	
Color	Silver	
Compressor Location	Top Mounted	
Construction	All Stainless Steel	
Door Style	Swing	
Door Type	Solid	
Features	Automatic Electric Defrost Digital Display Electronic Controller Energy Star Qualified Removable Magnetic Door Gaskets Self-Closing Doors	
Horsepower	12/7 HP	
Individual Shelf Capacity	120 lb.	
Installation Type	Freestanding	
Number of Compressors	1 Compressor	
Number of Doors	4 Doors	
Number of Sections	2 Sections	
Number of Shelves	6 Shelves	
Number of Tray Slides	6	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	3.2 oz.	
Refrigerant Type	R-290	
Temperature Range	-7 - 0 Degrees F	
Туре	Freezers	

Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco Z2-F4-K 54" solid half door stainless steel reach-in freezer, you receive performance you can depend on! A corrosion-resistant, all-stainless steel interior and exterior construction provides increased durability and a sleek appearance. The self-closing and stayopen locking solid doors give your staff the ability to more quickly and easily load your freezer when you get a delivery. Plus, a door open alarm alerts users to when the doors have been open for too long to keep your inventory safe and fresh.

This model features 6 plastic-coated steel shelves that fit in the freezer's pan slides. These slides fit full-size food pans (sold separately) and hold 33% more weight than shelf clips to make loading and unloading a breeze! The full-length U-shaped door handles further expedite the loading process. Since this model has half doors, you're able to keep other food cold if you're only opening half of the refrigerated space at a time. Thanks to the rear air duct, this model has exceptional air circulation. Included casters allow users to easily move and clean under the unit.

Designed to maintain temperatures from -7-0 degrees Fahrenheit, this freezer boasts a top-mounted 1 2/7 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit; meaning it'll get less dirty and won't be accidentally kicked. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller, automatic defrosting, and digital temperature control with digital display. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.