

ltem#:	1/8Z2R4LWMS		Project:	
	•		· · · · · · · · · · · · · · · · · · ·	
Otv.		Date:		Approval:

# Avantco Z2-R4-LWMS 54" VersaHub WiFi-Enabled Glass Half Door Stainless Steel Reach-In Refrigerator

Item#178Z2R4LWMS







## **Technical Data**

54 Inches	
32 3/16 Inches	
81 11/16 Inches	
49 3/8 Inches	
27 1/8 Inches	
56 11/16 Inches	
4.2 Amps	
60 Hz	
1 Phase	
115 Volts	

### **Features**

- VersaHub platform monitors unit failure, open doors, and temperature via text/email notifications
- Corrosion-resistant stainless steel interior and exterior
- Full-size food pan slides hold 33% more weight than standard shelf clips
- Rear air duct for exceptional circulation
- R-290 refrigerant; 115V; 1/2 hp

### Certifications



ETL Sanitation



Energy Star Qualified ETL, US To 5-15P







#### **Technical Data**

Wattage	456 Watts	
Access Type	Doors	
Capacity	43.93 cu. ft.	
Capacity (per Shelf)	120 lb.	
Casters	With Casters	
Color	Silver	
Compressor Location	Top Mounted	
Construction	All Stainless Steel	
Door Style	Swing	
Door Type	Glass	
Dutch Half Doors	With Dutch Half Doors	
Features	Automatic Electric Defrost Digital Display Electronic Controller Energy Star Qualified Removable Magnetic Door Gaskets VersaHub Compatible WiFi Enabled	
Horsepower	1/2 hp	
Installation Type	Freestanding	
Number of Compressors	1 Compressor	
Number of Doors	4 Doors	
Number of Shelves	6 Shelves	
Number of Tray Slides	5 5.16.135	
Number of fray Silues	6	
Plug Type		
	6	
Plug Type	6 NEMA 5-15P	
Plug Type Refrigerant Type	6 NEMA 5-15P R-290	
Plug Type Refrigerant Type Sections	6 NEMA 5-15P R-290 2 Sections	
Plug Type Refrigerant Type Sections Starting Amps	6 NEMA 5-15P R-290 2 Sections 12.6 Amps	
Plug Type Refrigerant Type Sections Starting Amps Starting Wattage	6 NEMA 5-15P R-290 2 Sections 12.6 Amps 1368 Watts	

#### **Notes & Details**

Your establishment relies on refrigeration for proper food safety, and with this Avantco Z2-R4-LWMS 54" VersaHub WiFi-Enabled glass half door stainless steel reach-in refrigerator, you receive performance you can depend on! A corrosion-resistant, all-stainless steel interior and exterior construction provides increased durability and a sleek appearance. This model uses the VersaHub platform to provide live notifications, history, and other WiFi-enabled updates. The glass doors provide optimal product visibility. Plus, a door open alarm alerts users to when the doors have been open for too long to keep your inventory safe and fresh.

This model features 6 plastic-coated steel shelves that fit in the refrigerator's pan slides. These slides fit full-size food pans (sold separately) and hold 33% more weight than shelf clips to make loading and unloading a breeze! The full-length U-shaped door handles further expedite the loading process. Since this model has half doors, you're able to keep other food cold if you're only opening half of the refrigerated space at a time. Thanks to the rear air duct, this model has exceptional air circulation. Included casters allow users to easily move and clean under the unit.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a top-mounted 1/2 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit; meaning it'll get less dirty and won't be accidentally kicked. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller, automatic defrosting, and digital temperature control with digital display. This item requires a 115V electrical connection for operation.



▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.