

Item #:	178Z2RWMS		Project:	
Otv.		Date:		Approval:

Avantco Z2-R-WMS 54" VersaHub WiFi-Enabled Solid Door Stainless Steel **Reach-In Refrigerator**

Item#178Z2RWMS







Technical Data

Width	54 Inches	
Depth	32 3/16 Inches	
Height	81 11/16 Inches	
Interior Width	49 3/8 Inches	
Interior Depth	27 1/8 Inches	
Interior Height	56 11/16 Inches	
Amps	4.2 Amps	
Hertz	60 Hz	
Phase	1 Phase	
Voltage	115 Volts	

Features

- VersaHub platform monitors unit failure, open doors, and temperature via text/email notifications
- Corrosion-resistant stainless steel interior and exterior
- Versatile shelf supports are 33% stronger than standard shelf clips and can hold full-size food pans
- Rear air duct for exceptional circulation
- R-290 refrigerant; 115V; 1/2 hp
- Note: only the refrigerator holds the ETL certification

Certifications



ETL Sanitation





Energy Star Qualified






Technical Data

Wattage	456 Watts	
Access Type	Doors	
Capacity	43.93 cu. ft.	
Capacity (per Shelf)	120 lb.	
Casters	With Casters	
Color	Silver	
Compressor Location	Top Mounted	
Construction	All Stainless Steel	
Door Style	Swing	
Door Type	Solid	
Dutch Half Doors	Without Dutch Half Doors	
Features	Automatic Electric Defrost Digital Display Electronic Controller Energy Star Qualified Removable Magnetic Door Gaskets Self-Closing Doors VersaHub Compatible WiFi Enabled	
Hinge Location	Left Right	
Horsepower	1/2 hp	
Installation Type	Freestanding	
Number of Compressors	1 Compressor	
	1 Compressor	
Number of Doors	1 Compressor 2 Doors	
Number of Doors Number of Shelves	·	
	2 Doors	
Number of Shelves	2 Doors 6 Shelves	
Number of Shelves Number of Tray Slides	2 Doors 6 Shelves 6	
Number of Shelves Number of Tray Slides Plug Type	2 Doors 6 Shelves 6 NEMA 5-15P	
Number of Shelves Number of Tray Slides Plug Type Refrigerant Type	2 Doors 6 Shelves 6 NEMA 5-15P R-290	
Number of Shelves Number of Tray Slides Plug Type Refrigerant Type Sections	2 Doors 6 Shelves 6 NEMA 5-15P R-290 2 Sections	
Number of Shelves Number of Tray Slides Plug Type Refrigerant Type Sections Starting Amps	2 Doors 6 Shelves 6 NEMA 5-15P R-290 2 Sections 12.6 Amps	
Number of Shelves Number of Tray Slides Plug Type Refrigerant Type Sections Starting Amps Starting Wattage	2 Doors 6 Shelves 6 NEMA 5-15P R-290 2 Sections 12.6 Amps 1368 Watts	
Number of Shelves Number of Tray Slides Plug Type Refrigerant Type Sections Starting Amps Starting Wattage Temperature Range	2 Doors 6 Shelves 6 NEMA 5-15P R-290 2 Sections 12.6 Amps 1368 Watts 33 - 40 Degrees F	

Plan View





Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco Z2-R-WMS 54" VersaHub WiFi-Enabled solid door stainless steel reach-in refrigerator, you receive performance you can depend on! A corrosion-resistant, all-stainless steel interior and exterior construction provides increased durability and a sleek appearance. This model uses the VersaHub platform to provide live notifications, history, and other WiFi-enabled updates. The self-closing and stay-open locking solid doors give your staff the ability to more quickly and easily load your refrigerator when you get a delivery. Plus, a door open alarm alerts users to when the doors have been open for too long to keep your inventory safe and fresh.

This model features 6 plastic-coated steel shelves that fit in the refrigerator's pan slides. These slides fit full-size food pans (sold separately) and hold 33% more weight than shelf clips to make loading and unloading a breeze! The full-length U-shaped door handles further expedite the loading process. Thanks to the rear air duct, this model has exceptional air circulation. Included casters allow users to easily move and clean under the unit.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a top-mounted 1/2 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit; meaning it'll get less dirty and won't be accidentally kicked. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller, automatic defrosting, and digital temperature control with digital display. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.