

ltem#:	178ZUC27FWMS		Project: _		
Otv:		Data	_	Ammaniali	
Utv:		Date:		Approval:	

Avantco ZUC-27F-WMS 27" VersaHub WiFi-Enabled Front Breathing **Undercounter Freezer**

Item #178ZUC27FWMS







Technical Data

Width	27 Inches	
Depth	29 1/2 Inches	
Height	35 3/16 Inches	
Interior Width	22 3/8 Inches	
Interior Depth	19 13/16 Inches	
Interior Height	23 1/2 Inches	
Work Surface Height	35 3/16 Inches	
Amps	3.6 Amps	
Hertz	60 Hz	
Phase	1 Phase	

Features

- VersaHub platform monitors unit failure, open doors, and temperature via text/email notifications
- Front breathing design provides exceptional airflow
- Easy-to-read digital temperature controller and auto-defrost function
- Stainless steel exterior and interior; foamed-in-place polyurethane insulation
- R-290 refrigerant; 115V; 1/5 hp
- Note: only the undercounter freezer holds the ETL certification

Certifications





ETL, US & Canada




ETL Sanitation



Technical Data

Voltage	115 Volts		
Wattage	235 Watts		
Access Type	Doors		
BTU (LBP)	880 BTU		
Capacity	5.4 cu. ft.		
Capacity (per Shelf)	88 lb.		
Casters	With Casters		
Compressor Location	Rear Mounted		
Compressor Style	Front Breathing		
Construction	Stainless Steel		
Door Style	Swing		
Door Type	Solid		
Features	Automatic Electric Defrost LED Lighting Removable Magnetic Door Gaskets Self-Closing Doors VersaHub Compatible WiFi Enabled		
Hinge Location	Right		
Horsepower	1/5 hp		
Number of Doors	1 Doors		
Number of Shelves	1 Shelf		
Plug Type	NEMA 5-15P		
Refrigerant Type	R-290		
Shelf Material	Epoxy-Coated Steel		
	Zpon, Course Coo.		
Starting Amps	10.8 Amps		
Starting Amps Starting Wattage	• •		
2 1	10.8 Amps		
Starting Wattage	10.8 Amps 705 Watts		
Starting Wattage Style	10.8 Amps 705 Watts Counter Height		

Plan View





Notes & Details

Make cold food storage as convenient as possible with this Avantco VersaHub WiFi-enabled undercounter freezer. With a spacious refrigerated portion readily accessible through its door, the unit opens up to a shelf to help you organize your ingredients and best utilize the 5.4 cu. ft. interior. Plus, because it accommodates up to 88 lb., the epoxycoated steel shelf is well equipped for holding heavy bulk ingredients, from frozen broccoli and cauliflower to frozen pork chops. This model uses the VersaHub platform to provide live notifications, history, and other WiFi-enabled updates.

The need for extra clearance is eliminated due to the convenient front-breathing deign, which allows the back and sides of the unit to be placed directly against a wall. This design provides exceptional airflow and helps to save space in your establishment. The self-closing and stay-open solid door allows users to load the unit quickly and easily after a delivery, while the recessed door handle and magnetic door gaskets further expedite the loading process. Plus, the bright LED interior lighting allows users to find what they're looking for with ease.

This corrosion-resistant unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint. This unit includes casters for easy mobility.

This freezer ensures optimal performance by operating with a 1/5 hp refrigeration system that circulates R-290 hydrocarbon refrigerant to maintain temperatures from -8 to 0 degrees Fahrenheit. R-290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to retain cold temperatures, which ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers!

Operation of the freezer is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. The controller's audible alarms alert you to temperatures too high or low, extended door opening, and to clean the unit's condenser. This undercounter unit requires a 115V electrical connection for operation.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.