

Item #:	178ZUC36FHC		Project:	
\bigcap +\rangle		Data:		Approval:

Avantco ZUC-36F-HC 36" Front Breathing Undercounter Freezer

Item#178ZUC36FHC







Technical Data

Width	36 3/16 Inches	
Depth	29 1/2 Inches	
Height	35 3/16 Inches	
Power Cord Length	98 7/16 Inches	
Interior Width	33 Inches	
Interior Depth	19 13/16 Inches	
Interior Height	23 1/2 Inches	
Work Surface Height	35 3/16 Inches	
Amps	4.1 Amps	
Hertz	60 Hz	

Features

- Front breathing design provides exceptional airflow
- Bright LED interior lighting
- Easy-to-read digital temperature controller and auto-defrost function
- Stainless steel exterior and interior; foamed-in-place polyurethane insulation
- R-290 refrigerant; 115V; 1/4 hp

Certifications





5-15P Online ETL, US & Canada Online ETL Sanitation






Technical Data

Phase	1 Phase	
Voltage	115 Volts	
Wattage	275 Watts	
Access Type	Doors	
BTU (LBP)	1276 BTU	
Capacity	8.7 cu. ft.	
Capacity (per Shelf)	88 lb.	
Casters	With Casters	
Compressor Location	Rear Mounted	
Compressor Style	Front Breathing	
Construction	Stainless Steel	
Door Style	Swing	
Door Type	Solid	
Features	Automatic Electric Defrost LED Lighting Removable Magnetic Door Gaskets Self-Closing Doors	
Hinge Location	Left Right	
Horsepower	1/4 hp	
Number of Doors	2 Doors	
Number of Shelves	2 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Shelf Material	Epoxy-Coated Steel	
Starting Amps	12.3 Amps	
Starting Wattage	825 Watts	
Style	Counter Height	
Temperature Range	-8 - 0 Degrees F	
Туре	Freezers Undercounter Freezers	

Plan View





Notes & Details

Make cold food storage as convenient as possible with this Avantco undercounter freezer. With a spacious refrigerated portion readily accessible through its doors, the unit opens up to two shelves to help you organize your ingredients and best utilize the 8.7 cu. ft. interior. Plus, because they accommodate up to 88 lb. each, the epoxy-coated steel shelves are well equipped for holding heavy bulk ingredients, from frozen broccoli and cauliflower to frozen pork chops.

The need for extra clearance is eliminated due to the convenient front-breathing deign, which allows the back and sides of the unit to be placed directly against a wall. This design provides exceptional airflow and helps to save space in your establishment. The self-closing and stay-open solid doors allow users to load the unit quickly and easily after a delivery, while the recessed door handles and magnetic door gaskets further expedite the loading process. Plus, the bright LED interior lighting allows users to find what they're looking for with ease.

This corrosion-resistant unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint. This unit includes casters for easy mobility.

This freezer ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R-290 hydrocarbon refrigerant to maintain temperatures from -8 to 0 degrees Fahrenheit. R-290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to retain cold temperatures, which ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers!

Operation of the freezer is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. The controller's audible alarms alert you to temperatures too high or low, extended door opening, and to clean the unit's condenser. This undercounter unit requires a 115V electrical connection for operation.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.