

Item #: 360SC40 Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco SC-40 Black Countertop Display Refrigerator with Swing Door

Item #360SC40



Technical Data

Width	15 3/4 Inches
Depth	16 3/8 Inches
Height	28 7/8 Inches
Power Cord Length	70 Inches
Sign Face Length	15 3/4 Inches
Interior Width	13 Inches
Interior Depth	10 1/4 Inches
Interior Height	18 1/2 Inches
Sign Face Height	7 1/8 Inches
Amps	1.6 Amps

Features

- Glass door and interior lighting increase impulse sales
- (3) adjustable shelves
- 1.5 cu. ft. interior
- 1/10 hp compressor
- 115V

Certifications



ETL, US



5-15P



Customizable

Technical Data

Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Access Type	Doors
Capacity	1.5 cu. ft.
Color	Black
Compressor Location	Top Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable Lighted Interior
Glass Style	Flat
Hinge Location	Right
Horsepower	1/10 HP
Installation Type	Countertop
Number of Doors	1 Doors
Number of Shelves	3 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	1 oz.
Refrigerant Type	R-600a
Temperature Range	33 - 40 Degrees F
Type	Countertop Refrigerators

Notes & Details

Showcase all of your patron's favorite grab and go items with this Avantco SC-40 countertop display refrigerator with glass door! Its lighted sign, clear glass door, and brightly lit interior puts items on full display to increase impulse sales at your convenience store, market, or deli. This unit allows you to Insert your own 15" x 7 1/8" graphic into the lighted sign to advertise beverages, pre-packaged snacks, and other impulse items.

- Interior lighting in center-front of model illuminates products; rear light switch and temperature controls are easy-to-reach
- (1) fully insulated, self-closing glass door with lock and key
- (3) adjustable wire shelves allow for complete control over shelving configuration and accommodate a variety of different sized products
- Durable, rust-proof black plastic superstructure ensures years of use
- Foamed in place polyurethane cell insulation helps maintain interior temperatures
- Top mounted, 1/10 hp compressor uses R-600a refrigerant
- Temperature range of 34 to 45 degrees Fahrenheit
- Requires a 115V electrical connection

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.