

Item #: 360SC40 Project: \_\_\_\_\_

Qty: \_\_\_\_\_ Date: \_\_\_\_\_ Approval: \_\_\_\_\_

## Avantco SC-40 Black Customizable Countertop Display Refrigerator with Swing Door

Item #360SC40




### Technical Data

Width	15 3/4 Inches
Depth	16 Inches
Height	28 11/16 Inches
Power Cord Length	74 13/16 Inches
Interior Width	12 Inches
Interior Depth	9 7/16 Inches
Interior Height	18 1/2 Inches
Amps	1.1 Amps
Hertz	60 Hz
Phase	1 Phase

### Features

- Glass door and interior lighting increase impulse sales
- (3) adjustable shelves
- 1.5 cu. ft. interior
- 1/10 hp compressor
- 115V

### Certifications



## Technical Data

Voltage	115 Volts
Wattage	700 Watts
Access Type	Doors
Capacity	1.5 cu. ft.
Color	Black
Compressor Location	Top Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable Lighted Interior
Glass Style	Flat
Hinge Location	Right
Horsepower	1/10 hp
Installation Type	Countertop
Number of Doors	1 Doors
Number of Shelves	3 Shelves
Refrigerant Capacity	1 oz.
Refrigerant Type	R-600a
Temperature Range	33 - 40 Degrees F
Type	Countertop Refrigerators

## Notes & Details

Showcase all of your patron's favorite grab and go items with this Avantco SC-40 countertop display refrigerator with glass door! Its lighted sign, clear glass door, and brightly lit interior puts items on full display to increase impulse sales at your convenience store, market, or deli. This unit allows you to Insert your own 15" x 7 1/8" graphic into the lighted sign to advertise beverages, pre-packaged snacks, and other impulse items.

- Interior lighting in center-front of model illuminates products; rear light switch and temperature controls are easy-to-reach
- (1) fully insulated glass door with lock and key
- (3) adjustable wire shelves allow for complete control over shelving configuration and accommodate a variety of different sized products
- Durable, rust-proof black plastic superstructure ensures years of use
- Foamed in place polyurethane cell insulation helps maintain interior temperatures
- Top mounted, 1/10 hp compressor uses R-600a refrigerant
- Temperature range of 34 to 45 degrees Fahrenheit
- Requires a 115V electrical connection

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).