



Item #: 447AP49R Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco A Plus AP-49R 55 3/8" Stainless Steel Solid Door Reach-In Refrigerator

Item #447AP49R



Technical Data

Width	55 3/8 Inches
Depth	31 1/8 Inches
Height	84 5/8 Inches
Power Cord Length	120 Inches
Door Opening Width	22 1/2 Inches
Interior Width	50 1/4 Inches
Shelf Width	24 5/8 Inches
Interior Depth	26 1/2 Inches
Shelf Depth	22 1/2 Inches
Height with Casters	84 3/4 Inches

Features

- Made in North America
- Type 430 stainless steel exterior with a type 201 interior; self-closing, stay-open, locking doors
- Digital control and automatic defrost; eco-mode to save energy and extend compressor life
- Includes 6 epoxy-coated adjustable shelves with an 80 lb. capacity each
- 115V, 1/3 hp, R-290 refrigerant

Certifications



ETL, US



Imported from Mexico



ETL Sanitation




5-15P

Avantco Refrigeration

Technical Data

Interior Height	56 1/4 Inches
Amps	3 Amps
Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Access Type	Doors
Capacity	49 cu. ft.
Casters	With Casters
Color	Silver
Compressor Location	Bottom Mounted
Construction	All Stainless Steel
Door Style	Swing
Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors
Features	Self-Closing Doors
Handle Material	Stainless Steel
Hinge Location	Left/Right
Horsepower	1/3 HP
Individual Shelf Capacity	80 lb.
Installation Type	Freestanding
Number of Compressors	1 Compressor
Number of Doors	2 Doors
Number of Shelves	6 Shelves
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Sections	2 Sections
Temperature Range	32 - 38 Degrees F
Type	Refrigerators

Plan View





Notes & Details

Made in North America, this Avantco A Plus AP-49R 55 3/8" solid door refrigerator gives your establishment the performance you need and rely on for proper food safety! Designed to suit a commercial environment, this refrigerator features a durable type 403 stainless steel exterior and a type 201 stainless steel interior for corrosion-resistance and easy cleaning.

Equipped with Avantco's A-Plus Eco Mode, this unit can automatically detect door openings and will enter a power-saving cycle in off hours. This system will reduce your energy cost without sacrificing consistent product temperature! This digital controller lets you set and adjust your refrigerator as needed, plus the automatic defrost helps to minimize maintenance.

For convenience, 6 epoxy coated shelves can be easily adjusted inside the cabinet to meet your unique storage needs. Each shelf can hold up to 80 lb. for storing heavy loads of pre-made foods or ingredients. For optimal temperature retention, the entire cabinet is insulated. This refrigerator also comes with casters so that you can easily move it for easy cleaning and maintenance.

For easy access to your refrigerator, this unit comes with two solid doors with both stay-open and self-closing closing features for the convenience of your employees. Plus, the doors can be locked to protect your stock overnight or during off hours.

Designed to maintain temperatures from 32 to 38 degree Fahrenheit, this refrigerator boasts a 1/3 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. This item requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.p65warnings.ca.gov.